

**Description**

IP66. Class I. IK08. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Mount permits 350° rotation and 180° tilt.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Colors	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown
Ingress protection	IP66			
Impact resistance	IK08			






### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
--------------	---




### Additional information

Length x Width (inches)	8.46 x 6.89
-------------------------	-------------

**Options**

Light distribution	Color temperature	Nominal Watt
 [B]	 3000K	18 W 26 W
 [M]	 4000K	
 [EE]		

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[B]</p>	161-5876	LED-6/18W/3000K	2018.8 lm	18 W	80
	161-5878	LED-6/18W/4000K	2112.7 lm	18 W	80
	161-5877	LED-6/26W/3000K	2582.2 lm	26 W	80
	161-5879	LED-6/26W/4000K	2699.6 lm	26 W	80
 <p>[EE]</p>	161-5884	LED-6/18W/3000K	2165.6 lm	18 W	80
	161-5886	LED-6/18W/4000K	2266.4 lm	18 W	80
	161-5885	LED-6/26W/3000K	2770 lm	26 W	80
	161-5887	LED-6/26W/4000K	2895.9 lm	26 W	80
 <p>[M]</p>	161-5880	LED-6/18W/3000K	2167.2 lm	18 W	80
	161-5882	LED-6/18W/4000K	2268 lm	18 W	80
	161-5881	LED-6/26W/3000K	2772 lm	26 W	80
	161-5883	LED-6/26W/4000K	2898 lm	26 W	80