




**Description**

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board.

Including 0,4 m of flexible cable enclosed in stainless conduit, in-line connector and mounting clamp for installation to RAIL66 mounting system.



## Specifications

### Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Safety glass lens			
Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9016</b>	<b>RAL7016</b>
	Signal black	White aluminium	Traffic white	Anthracite grey
	<b>RAL9007</b>			
	Grey aluminium			
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

### Additional information





Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------




**Options**

**Light distribution**

**Colour temperature**





**Nominal Watt**

- 
[M] symmetric, medium beam
- 
[EES] symmetric, very narrow beam, sharp cut-off
- 
[B] symmetric, wide beam
- 
[EE] symmetric, very narrow beam

- 
3000K
- 
4000K
- 
2700K

12 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	145-0297	LED-6/12W/2700K	1254.2 lm	12 W	80
	145-0088	LED-6/12W/3000K	1347.1 lm	12 W	80
	145-0089	LED-6/12W/4000K	1440 lm	12 W	80
[B] symmetric, wide beam					
	145-0299	LED-6/12W/2700K	1393.3 lm	12 W	80
	145-0091	LED-6/12W/3000K	1496.5 lm	12 W	80
	145-0092	LED-6/12W/4000K	1599.7 lm	12 W	80
[EE] symmetric, very narrow beam					
	145-0300	LED-6/12W/2700K	1499.6 lm	12 W	80
	145-0046	LED-6/12W/3000K	1610.7 lm	12 W	80
	145-0047	LED-6/12W/4000K	1721.8 lm	12 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	145-0298	LED-6/12W/2700K	1407.5 lm	12 W	80
	145-0043	LED-6/12W/3000K	1511.8 lm	12 W	80
	145-0044	LED-6/12W/4000K	1616.1 lm	12 W	80
[M] symmetric, medium beam					