

Description

IP66, Class I. IK07. Marine-grade die-cast aluminium alloy.
5CE superior corrosion protection + primer including
PCS hardware. Silicone CCG® Controlled Compression
Gasket. Safety glass lens. PMMA-LED lens array.
Remote 240v gear to be ordered separately.

2700 K option available on request.

Specifications

Material description

Body	Marine-grade die-cast aluminium alloy		
Lens	Safety glass lens		
Colours	RAL9004	RAL9006	RAL9007
	Signal black	White aluminium	Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

Electrical description

Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.
-------------------	--

Additional information

Options

Light distribution Colour temperature Nominal Watt



[B]



3000K

12 W



[M]



4000K







[EE]



[EES]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	145-0117	LED-6/12W/3000K	1347.1 lm	12 W	80
	145-0118	LED-6/12W/4000K	1440 lm	12 W	80
[B]					
	145-0123	LED-6/12W/3000K	1496.5 lm	12 W	80
	145-0123	LED-6/12W/3000K	1496.5 lm	12 W	80
	145-0124	LED-6/12W/4000K	1599.7 lm	12 W	80
	145-0124	LED-6/12W/4000K	1599.7 lm	12 W	80
[EE]					
	145-0126	LED-6/12W/3000K	1610.7 lm	12 W	80
	145-0126	LED-6/12W/3000K	1610.7 lm	12 W	80
	145-0127	LED-6/12W/4000K	1721.8 lm	12 W	80
	145-0127	LED-6/12W/4000K	1721.8 lm	12 W	80
[EES]					
	145-0120	LED-6/12W/3000K	1511.8 lm	12 W	80
	145-0121	LED-6/12W/4000K	1616.1 lm	12 W	80
[M]					