





Description

IP55. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire.



Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Luminaire body and lens frame constructed in die-cast aluminum.			
Lens	Clear tempered glass lens.			
Colors	RAL9004	RAL9016	RAL8019	RAL9007
	Signal black	Traffic white	Grey brown	Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket			
Fasteners	PCS polymer coated stainless steel			
Impact resistance	IK07			
Corrosion resistance	5CE			







Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral driver in thermally separated compartment.





Additional information

Diameter (inches)	4.13
Listings	ETL listed. Suitable for wet locations.
Lifetime	Ta less than 25 deg C.

Options

Light distribution	Color temperature	Nominal Watt
 [M]	 3000K	12 W
 [EE]	 4000K	
 [EES]		
 [B]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	145-9383	LED-6/12W/3000K	1347.1 lm	12 W	80
	145-9385	LED-6/12W/4000K	1440 lm	12 W	80
[B]					
	145-9375	LED-6/12W/3000K	1496.5 lm	12 W	80
	145-9378	LED-6/12W/4000K	1599.7 lm	12 W	80
[EE]					
	145-9382	LED-6/12W/3000K	1610.7 lm	12 W	80
	145-9384	LED-6/12W/4000K	1721.8 lm	12 W	80
[EES]					
	145-9374	LED-6/12W/3000K	1511.8 lm	12 W	80
	145-9377	LED-6/12W/4000K	1616.1 lm	12 W	80
[M]					