

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during the installation. 0-10V Dimming comes standard with luminaire.

Knuckle permits 350° horizontal and 90° vertical aiming of optics.

Specify product with 7 Digit product code - Finish Color. (Other accessories, such as mounting, optical, and electrical, must be specified separately.)

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessories)

Specifications

Material description

Colors

Ingress protection IP66

Impact resistance IK07

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Additional information

Options

Light distribution

Color temperature

Nominal Watt



[W] bi-symmetric, wide beam



[M] symmetric, medium beam







[VN] symmetric, very narrow beam



[VNS] symmetric, very narrow beam, sharp cut-off

0 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	145-6512		2998.6 lm	0 W	80
	145-6513		3205.4 lm	0 W	80
[M] symmetric, medium beam					
	145-6510		2883.7 lm	0 W	80
	145-6511		3082.5 lm	0 W	80
[VN] symmetric, very narrow beam					
	145-6508		3077.9 lm	0 W	80
	145-6509		3290.2 lm	0 W	80
[VNS] symmetric, very narrow beam, sharp cut-off					
	145-6514		2709.2 lm	0 W	80
	145-6515		2896 lm	0 W	80
[W] bi-symmetric, wide beam					