

Description

IP66, Class I. IK07. Marine-grade die-cast aluminium alloy.
5CE superior corrosion protection + primer including
PCS hardware. Silicone CCG® Controlled Compression
Gasket. Safety glass lens. PMMA-LED lens array.
Remote 240 V gear to be ordered separately.

2700 K option available on request.

Specifications

Material description







Body	Marine-grade die-cast aluminium alloy		
Lens	Safety glass lens		
Colours	RAL9004	RAL9006	RAL9007
	Signal black	White aluminium	Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

Electrical description





Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.
-------------------	--

Additional information

Options

Light distribution	Colour temperature	Nominal Watt
 [B]	 3000K	24 W
 [M]	 4000K	
 [EE]	RGBW	
 [EES]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	146-0597	LED-12/24W/3000K	2709.2 lm	24 W	80
	146-0598	LED-12/24W/4000K	2896 lm	24 W	80
	146-8360	LED-12/24W/RGBW	1318.9 lm	24 W	80
[B]					
	146-0603	LED-12/24W/3000K	2883.7 lm	24 W	80
	146-0603	LED-12/24W/3000K	2883.7 lm	24 W	80
	146-0604	LED-12/24W/4000K	3082.5 lm	24 W	80
	146-0604	LED-12/24W/4000K	3082.5 lm	24 W	80
[EE]					
	146-8361	LED-12/24W/RGBW	1461.3 lm	24 W	80
	146-0606	LED-12/24W/3000K	3077.9 lm	24 W	80
	146-0606	LED-12/24W/3000K	3077.9 lm	24 W	80
	146-0607	LED-12/24W/4000K	3290.2 lm	24 W	80
[EES]					
	146-0607	LED-12/24W/4000K	3290.2 lm	24 W	80
	146-0600	LED-12/24W/3000K	2998.6 lm	24 W	80
	146-0601	LED-12/24W/4000K	3205.4 lm	24 W	80
	146-8362	LED-12/24W/RGBW	1599.4 lm	24 W	80
[M]					