

Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory- sealed and does not need to be opened during the installation.

Optional 2200 K version available. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Safety glass lens			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey
	RAL9007 Grey aluminium			
Gasket	Silicone rubber gaskets			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			

Electrical description








Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

Additional information





Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution Colour temperature Nominal Watt

	[M]		3000K	24 W
	[EES]		4000K	
	[B]		2700K	
	[EE]			

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	146-0796	LED-12/24W/2700K	2522.3 lm	24 W	80
	146-0494	LED-12/24W/3000K	2709.2 lm	24 W	80
	146-0495	LED-12/24W/4000K	2896 lm	24 W	80
[B]					
	146-0951	LED-12/24W/2700K	2684.8 lm	24 W	80
	146-0951	LED-12/24W/2700K	2684.8 lm	24 W	80
	146-0497	LED-12/24W/3000K	2883.7 lm	24 W	80
	146-0497	LED-12/24W/3000K	2883.7 lm	24 W	80
	146-0498	LED-12/24W/4000K	3082.5 lm	24 W	80
[EE]					
	146-0971	LED-12/24W/2700K	2865.6 lm	24 W	80
	146-0971	LED-12/24W/2700K	2865.6 lm	24 W	80
	146-0402	LED-12/24W/3000K	3077.9 lm	24 W	80
	146-0402	LED-12/24W/3000K	3077.9 lm	24 W	80
	146-0403	LED-12/24W/4000K	3290.2 lm	24 W	80
[EES]					
	146-0922	LED-12/24W/2700K	2791.8 lm	24 W	80
	146-0922	LED-12/24W/2700K	2791.8 lm	24 W	80
	146-0399	LED-12/24W/3000K	2998.6 lm	24 W	80
	146-0399	LED-12/24W/3000K	2998.6 lm	24 W	80
	146-0400	LED-12/24W/4000K	3205.4 lm	24 W	80
[M]					
	146-0400	LED-12/24W/4000K	3205.4 lm	24 W	80