




**Description**

IP55, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Optional 2200 K version available. Factory installed LED circuit board.

Knuckle permits 350° horizontal and 90° vertical aiming of optics.



## Specifications

### Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Safety glass lens			
Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey
	<b>RAL9007</b> Grey aluminium			
Gasket	Silicone rubber gaskets			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP55			
Impact resistance	IK07			
Corrosion resistance	5CE			

### Electrical description








Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	1/2 kV
Energy efficiency	C-D (Light source)

### Additional information





Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**

**Light distribution    Colour temperature    Nominal Watt**

	[M]		3000K	48 W
	[EES]		4000K	
	[B]		2700K	
	[EE]			

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	146-0976	LED-24/48W/2700K	5016.9 lm	48 W	80
	146-7066	LED-24/48W/3000K	5388.5 lm	48 W	80
	146-7067	LED-24/48W/4000K	5760.1 lm	48 W	80
[B]					
	146-0978	LED-24/48W/2700K	5573.3 lm	48 W	80
	146-0978	LED-24/48W/2700K	5573.3 lm	48 W	80
	146-7068	LED-24/48W/3000K	5986.1 lm	48 W	80
	146-7068	LED-24/48W/3000K	5986.1 lm	48 W	80
	146-7069	LED-24/48W/4000K	6398.9 lm	48 W	80
[EE]					
	146-0979	LED-24/48W/2700K	5998.4 lm	48 W	80
	146-0979	LED-24/48W/2700K	5998.4 lm	48 W	80
	146-7056	LED-24/48W/3000K	6442.7 lm	48 W	80
	146-7056	LED-24/48W/3000K	6442.7 lm	48 W	80
	146-7057	LED-24/48W/4000K	6887 lm	48 W	80
[EES]					
	146-0977	LED-24/48W/2700K	5630.1 lm	48 W	80
	146-0977	LED-24/48W/2700K	5630.1 lm	48 W	80
	146-7054	LED-24/48W/3000K	6047.2 lm	48 W	80
	146-7054	LED-24/48W/3000K	6047.2 lm	48 W	80
	146-7055	LED-24/48W/4000K	6464.2 lm	48 W	80
[M]					
	146-7055	LED-24/48W/4000K	6464.2 lm	48 W	80