

Description

Profile Projector [FP] for framing applications, polygon shape. Spherical and aspherical, double flat convex lens system.

IP66, Class III. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Electronic control gear in separate gear box (constant current), prewired. Gearbox to be ordered separately. One factory installed flange plug M8 x 1.5. Cable length 10 ft. CAD-optimised optics for superior illumination and glare control. Factory-installed LED circuit board.



Specifications

Material description

Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Power supply	220-240V / 50-60 Hz
Energy efficiency	D-E (Light source)

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution



[FP] symmetric Framing-Projector

Colour temperature



2700K



3000K




4000K

Nominal Watt

6 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [FP] symmetric Framing-Projector	139-2752	LED-1/6W/2700K	394.6 lm	6 W	80
	139-2752	LED-1/6W/2700K	373.3 lm	6 W	80
	139-2753	LED-1/6W/3000K	394.6 lm	6 W	80
	139-2753	LED-1/6W/3000K	373.3 lm	6 W	80
	139-2754	LED-1/6W/4000K	424 lm	6 W	80
	139-2754	LED-1/6W/4000K	401.1 lm	6 W	80