

Description

IP66, Class III. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One factory installed flange plug M8 x 1.5. Cable length 10 ft. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board.
 REMOTE DRIVER IN SEPARATE DRIVER BOX (CONSTANT CURRENT), PREWIRED; TO BE ORDERED SEPARATELY.
 Maximum one internal optical accessory possible, to be specified at time of ordering.
 Specify product with 7 Digit product code - Finish Color.
 Accessories, such as mounting, optical, and electrical, must be specified separately.
 Example: XXX-XXXX - 9004 (Black)
 + XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			









Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Remote 120-277V , 0-10V (Dimming to be ordered separately)
Energy efficiency	D-E (Light source)






Additional information

Diameter (inches)	2.95
Windage	0.065
Lifetime	Ta=40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B]	 2700K	6 W
 [M]	 3000K	
 [E]	 4000K	
 [EE]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	139-2435	LED-1/6W/2700K	518.4 lm	6 W	80
	139-2436	LED-1/6W/3000K	518.4 lm	6 W	80
	139-2437	LED-1/6W/4000K	557.1 lm	6 W	80
[B]	<hr/>				
	139-2441	LED-1/6W/2700K	567.7 lm	6 W	80
	139-2442	LED-1/6W/3000K	567.7 lm	6 W	80
	139-2443	LED-1/6W/4000K	610.1 lm	6 W	80
[E]	<hr/>				
	139-2444	LED-1/6W/2700K	568.2 lm	6 W	80
	139-2445	LED-1/6W/3000K	568.2 lm	6 W	80
	139-2446	LED-1/6W/4000K	610.6 lm	6 W	80
[EE]	<hr/>				
	139-2447	LED-1/6W/2700K	516.6 lm	6 W	80
	139-2448	LED-1/6W/3000K	516.6 lm	6 W	80
	139-2449	LED-1/6W/4000K	558.6 lm	6 W	80
[EES]	<hr/>				
	139-2438	LED-1/6W/2700K	544.8 lm	6 W	80
	139-2439	LED-1/6W/3000K	544.8 lm	6 W	80
	139-2440	LED-1/6W/4000K	585.5 lm	6 W	80
[M]	<hr/>				