

Description

IP66, Class III. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One factory installed flange plug M8 x 1.5. Cable length 4 ft. Integral driver in separate driver box (constant current), prewired; to be ordered separately. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board. Tunable White technology. DMX interface.

Maximum one internal optical accessory possible, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

| | | | | |
|--------------------|--------------------------------|----------------------------------|---------------------------------|------------------------------|
| Colors | RAL9004 Signal black | RAL9007 Grey aluminium | RAL9016 Traffic white | RAL8019 Grey brown |
| Ingress protection | IP66 | | | |
| Impact resistance | IK07 | | | |




Electrical description

| | |
|-------------------|---------------------|
| Power supply | 220-240V / 50-60 Hz |
| Driver / Ballast | 120-277V DMX |
| Energy efficiency | D (Light source) |




Additional information

| | |
|----------|------------------------|
| Windage | 0.065 |
| Lifetime | Ta=25° L90B10 > 90000h |

Options

| Light distribution | Color temperature | Nominal Watt |
|--|-------------------|--------------|
|  [W] bi-symmetric, wide beam | 2200-6000K | 6 W |
|  [M] symmetric, medium beam | | |
|  [N] bi-symmetric, narrow beam | | |

Configurations

| Light distribution | Part ID | Light source | Delivered lumens | Rated input power | CRI |
|---|-------------|---------------------|------------------|-------------------|-----|
|  <p>[M] symmetric, medium beam</p> | 139-2451_us | LED-1/6W/2200-6000K | 321.1 lm | 6 W | 80 |
|  <p>[N] bi-symmetric, narrow beam</p> | 139-2452_us | LED-1/6W/2200-6000K | 326.9 lm | 6 W | 80 |
|  <p>[W] bi-symmetric, wide beam</p> | 139-2450_us | LED-1/6W/2200-6000K | 317.8 lm | 6 W | 80 |