

Description

IP66, Class III. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One factory installed flange plug M8 x 1.5. Cable length 4 ft. Integral driver in separate driver box (constant current), prewired; to be ordered separately. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board. Tunable White technology. DMX interface.

Maximum one internal optical accessory possible, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	120-277V DMX
Energy efficiency	D (Light source)

Additional information

Diameter (inches)	2.95
Windage	0.065
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution **Color temperature** **Nominal Watt**



[B]

2200-6000K

4 W






[M]



[E]

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[B]</p>	139-2450	LED-1/4W/2200-6000K	317.8 lm	4 W	80
 <p>[E]</p>	139-2452	LED-1/4W/2200-6000K	326.9 lm	4 W	80
 <p>[M]</p>	139-2451	LED-1/4W/2200-6000K	321.1 lm	4 W	80