




Description

Profile Projector [ZP] for zoom spot. Spherical and aspherical, double flat convex lens system.

IP66, Class III. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Electronic control gear in separate gear box (constant current), prewired. Gearbox to be ordered separately. One factory installed flange plug M8 x 1.5. Cable length 10 ft. CAD-optimised optics for superior illumination and glare control. Factory-installed LED circuit board.



Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Power supply	220-240V / 50-60 Hz
Energy efficiency	D-E (Light source)

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
----------	----------------------------

Options

Light distribution



[ZP] symmetric Zoom-Projector


Color temperature

Nominal Watt

- 2700K
- 3000K
- 4000K

6 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[ZP] symmetric Zoom-Projector</p>	139-2746	LED-1/6W/2700K	394.6 lm	6 W	80
	139-2746	LED-1/6W/2700K	373.3 lm	6 W	80
	139-2747	LED-1/6W/3000K	394.6 lm	6 W	80
	139-2747	LED-1/6W/3000K	373.3 lm	6 W	80
	139-2748	LED-1/6W/4000K	424 lm	6 W	80
	139-2748	LED-1/6W/4000K	401.1 lm	6 W	80