




Description

Profile Projector [ZP] for zoom spot. Spherical and aspherical, double flat convex lens system.

IP66, Class III. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Electronic control gear in separate gear box (constant current), prewired. Gearbox to be ordered separately. One factory installed flange plug M8 x 1.5. Cable length 10 ft. CAD-optimised optics for superior illumination and glare control. Factory-installed LED circuit board.



Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description


Power supply	220-240V / 50-60 Hz
Energy efficiency	D-E (Light source)

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------


Options

Light distribution **Colour temperature** **Nominal Watt**



6 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[ZP]</p>	139-2746	LED-1/6W/2700K	394.6 lm	6 W	80
	139-2746	LED-1/6W/2700K	373.3 lm	6 W	80
	139-2747	LED-1/6W/3000K	394.6 lm	6 W	80
	139-2747	LED-1/6W/3000K	373.3 lm	6 W	80
	139-2748	LED-1/6W/4000K	424 lm	6 W	80
	139-2748	LED-1/6W/4000K	401.1 lm	6 W	80