




Description

RGBW/RGBA Colour Changer Profile Projector [FP] for framing applications, polygon shape. Spherical and aspherical, double flat convex lens system.

IP66, Class III. IK05. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Electronic control gear in separate gearbox (medium), prewired. Glass LED lens array. Factory installed LED circuit board. DMX interface.



Specifications

Material description

Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Ingress protection	IP66		
Impact resistance	IK05		

Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	6/6 kV (optional SP10 in separate gearbox, large)
Energy efficiency	G (Light source)

Additional information

Lifetime	T _a =40° L70B50 > 50000h
----------	-------------------------------------

Options

Light distribution



[FP] symmetric Framing-Projector

Colour temperature


4000K+RGBW

RGBA

Nominal Watt

15 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[FP] symmetric Framing-Projector</p>	139-2490	LED-1/15W/4000K+RGBW	381.2 lm	15 W	80
	139-2490	LED-1/15W/4000K+RGBW	572.1 lm	15 W	80
	139-2491	LED-1/15W/RGBA	352.6 lm	15 W	80
	139-2491	LED-1/15W/RGBA	529.2 lm	15 W	80