




Description

RGBW/RGBA Colour Changer Profile Projector [ZP] for zoom spot. Spherical and aspherical, double flat convex lens system. Colour Boost Technology.



IP66, Class III. IK05. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Electronic control gear in separate gearbox (medium), prewired. Glass LED lens array. Factory installed LED circuit board. DMX interface.

Specifications

Material description

Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK05			

Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	6/6 kV (optional SP10 in separate gearbox, large)
Energy efficiency	G (Light source)

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

Options

Light distribution **Colour temperature** **Nominal Watt**




4000K+RGBW

15 W

RGBA

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [ZP]	139-2484	LED-1/15W/4000K+RGBW	381.2 lm	15 W	80
	139-2484	LED-1/15W/4000K+RGBW	572.1 lm	15 W	80
	139-2485	LED-1/15W/RGBA	352.6 lm	15 W	80
	139-2485	LED-1/15W/RGBA	529.2 lm	15 W	80