

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Integral driver, thermally separated. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.

True Amber upon request.

Maximum one internal optical accessory possible, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)			
Ingress protection	IP66			
Impact resistance	IK07			









Electrical description

Power supply	Integral [ECG] LED driver in 120-277V
Driver / Ballast	Integral 0-10V LED Driver
Surge protection	SP10
Energy efficiency	D-E (Light source)






Additional information

Diameter (inches)	5.90
Listings	Contact WE-EF USA for ETL/UL certification status.
Windage	0.194 ft ²
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B]	 2700K	12 W 9 W
 [M]	 3000K	
 [E]	 4000K	
 [EE]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	139-2391	LED-3/12W/2700K	1212.4 lm	12 W	80
	139-2389	LED-3/12W/3000K	1212.4 lm	12 W	80
	139-2390	LED-3/12W/4000K	1311.4 lm	12 W	80
[B]					
	139-2397	LED-3/12W/2700K	1187.1 lm	12 W	80
	139-2395	LED-3/12W/3000K	1187.1 lm	12 W	80
	139-2396	LED-3/12W/4000K	1284 lm	12 W	80
[E]					
	139-2400	LED-3/12W/2700K	1306.4 lm	12 W	80
	139-2400	LED-3/12W/2700K	1306.4 lm	12 W	80
	139-2398	LED-3/12W/3000K	1306.4 lm	12 W	80
	139-2398	LED-3/12W/3000K	1306.4 lm	12 W	80
	139-2399	LED-3/12W/4000K	1413 lm	12 W	80
	139-2399	LED-3/12W/4000K	1413 lm	12 W	80
[EE]					
	139-2387	LED-3/9W/4000K	950.2 lm	9 W	80
	139-2403	LED-3/12W/2700K	1184.4 lm	12 W	80
	139-2403	LED-3/12W/2700K	1184.4 lm	12 W	80
	139-2401	LED-3/12W/3000K	1184.4 lm	12 W	80
	139-2401	LED-3/12W/3000K	1184.4 lm	12 W	80
	139-2402	LED-3/12W/4000K	1275.6 lm	12 W	80
	139-2402	LED-3/12W/4000K	1275.6 lm	12 W	80
[EES]					
	139-2394	LED-3/12W/2700K	1289.4 lm	12 W	80
	139-2392	LED-3/12W/3000K	1289.4 lm	12 W	80
	139-2393	LED-3/12W/4000K	1394.6 lm	12 W	80
[M]					