

Description

Profile Projector [GP] for projection of gobos on a surface. Spherical and aspherical, double flat convex lens system. Gobo motif on request, to be ordered separately.

IP66, Class I. IK05. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request.

Integral EC electronic converter in thermally-separated compartment. Glass LED lens array. Factory installed LED circuit board.

Custom-made gobos (outside diameter 46.6 mm, max. printable area d = 38 mm) available on request.

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29
https://we-ef.com/asia

Specifications

Material description

Colours	RAL9004	RAL9007	RAL7016	RAL9016
	Signal black	Grey aluminium	Anthracite grey	Traffic white
Ingress protection	IP66			
Impact resistance	IK05			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	6/6 kV (optional SP10, only for ON/OFF)
Energy efficiency	F (Light source)

Additional information

Lifetime	Ta=25° L70B50 > 50000h

Options

Light distribution	Colour temperature	Nominal Watt
[GP] symmetric Gobo-Projector	2700K	18 W 26 W
	3000K	
	4000K	

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29
https://we-ef.com/asia

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[GP] symmetric Gobo-Projector	139-2503	LED-1/18W/2700K	778.3 lm	18 W	80
	139-2503	LED-1/18W/2700K	812.4 lm	18 W	80
	139-2498	LED-1/18W/3000K	805.1 lm	18 W	80
	139-2498	LED-1/18W/3000K	840.4 lm	18 W	80
	139-2499	LED-1/18W/4000K	848.7 lm	18 W	80
	139-2499	LED-1/18W/4000K	885.9 lm	18 W	80
	139-2506	LED-1/26W/2700K	1070.1 lm	26 W	80
	139-2506	LED-1/26W/2700K	1117 lm	26 W	80
	139-2479	LED-1/26W/3000K	1105.4 lm	26 W	80
	139-2479	LED-1/26W/3000K	1153.8 lm	26 W	80
	139-2480	LED-1/26W/4000K	1164.1 lm	26 W	80
	139-2480	LED-1/26W/4000K	1215.1 lm	26 W	80

WE-EF LIGHTING (Thailand) Co., Ltd.
57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29
https://we-ef.com/asia