

Description

Profile Projector [GP] for projection of gobos on a surface. Spherical and aspherical, double flat convex lens system.

Gobo size T. Gobo outside diameter 46,6 mm, max. printable area d = 38 mm.

IP66, Class I. IK05. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Integral driver, thermally separated. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK05			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V
Driver / Ballast	Integral 0-10V LED Driver
Surge protection	6/6 kV (optional SP10, only for ON/OFF)
Energy efficiency	F (Light source)

Additional information

Listings	Contact WE-EF USA for ETI/UL Certification status.
Lifetime	Ta=25°/40° L70B50 > 50000h

Options

Light distribution



[GP] symmetric Gobo-Projector

Color temperature

Nominal Watt



2700K

18 W

26 W




3000K



4000K

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[GP] symmetric Gobo-Projector</p>	139-2503_us	LED-1/18W/2700K	778.3 lm	18 W	80
	139-2503_us	LED-1/18W/2700K	812.4 lm	18 W	80
	139-2498_us	LED-1/18W/3000K	805.1 lm	18 W	80
	139-2498_us	LED-1/18W/3000K	840.4 lm	18 W	80
	139-2499_us	LED-1/18W/4000K	848.7 lm	18 W	80
	139-2499_us	LED-1/18W/4000K	885.9 lm	18 W	80
	139-2506_us	LED-1/26W/2700K	1070.1 lm	26 W	80
	139-2506_us	LED-1/26W/2700K	1117 lm	26 W	80
	139-2479_us	LED-1/26W/3000K	1105.4 lm	26 W	80
	139-2479_us	LED-1/26W/3000K	1153.8 lm	26 W	80
	139-2480_us	LED-1/26W/4000K	1164.1 lm	26 W	80
	139-2480_us	LED-1/26W/4000K	1215.1 lm	26 W	80