

Description

Profile Projector [ZP] for zoom spot. Spherical and aspherical, double flat convex lens system.

IP66, Class I. IK05. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Integral driver, thermally separated. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK05			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V
Driver / Ballast	Integral 0-10V LED Driver
Surge protection	6/6 kV (optional SP10, only for ON/OFF)
Energy efficiency	F (Light source)

Additional information

Listings	Contact WE-EF USA for ETL/UL Certification status
Lifetime	Ta=25°/40° L70B50 > 50000h

Options

Light distribution



[ZP] symmetric Zoom-Projector

Color temperature

Nominal Watt



2700K

18 W

26 W




3000K



4000K

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[ZP] symmetric Zoom-Projector</p>	139-2502_us	LED-1/18W/2700K	1190.3 lm	18 W	80
	139-2502_us	LED-1/18W/2700K	1286.6 lm	18 W	80
	139-2496_us	LED-1/18W/3000K	1231.4 lm	18 W	80
	139-2496_us	LED-1/18W/3000K	1330.9 lm	18 W	80
	139-2497_us	LED-1/18W/4000K	1403 lm	18 W	80
	139-2505_us	LED-1/26W/2700K	1636.7 lm	26 W	80
	139-2505_us	LED-1/26W/2700K	1769 lm	26 W	80
	139-2477_us	LED-1/26W/3000K	1690.6 lm	26 W	80
	139-2477_us	LED-1/26W/3000K	1827.3 lm	26 W	80
	139-2478_us	LED-1/26W/4000K	1780.3 lm	26 W	80
	139-2478_us	LED-1/26W/4000K	1924.3 lm	26 W	80