



**Description**

Profile Projector [ZP] for zoom spot. Spherical and aspherical, double flat convex lens system.

IP66, Class I. Class II on request. IK05. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Integral electronic control gear, thermally separated. Glass LED lens array. Factory installed LED circuit board.



## Specifications

### Material description

|                    |                                |                                   |                                  |
|--------------------|--------------------------------|-----------------------------------|----------------------------------|
| Colours            | <b>RAL9004</b><br>Signal black | <b>RAL9006</b><br>White aluminium | <b>RAL9007</b><br>Grey aluminium |
| Ingress protection | IP66                           |                                   |                                  |
| Impact resistance  | IK05                           |                                   |                                  |

### Electrical description

|                   |   |
|-------------------|---|
| Power supply      | 220-240V / 50-60 Hz   |
| Driver / Ballast  | Standard. Optional DALI version available. To be specified at time of ordering. |
| Surge protection  | 6/6 kV (optional SP10, only for ON/OFF)   |
| Energy efficiency | F (Light source)  |

### Additional information

|          |                        |
|----------|------------------------|
| Lifetime | Ta=40° L70B50 > 50000h |
|----------|------------------------|

**Options**

**Light distribution**    **Colour temperature**    **Nominal Watt**




2700K

18 W

26 W




3000K



4000K

## Configurations

| Light distribution  | Part ID  | Light source    | Rated lumens | Rated input power | CRI |
|---|----------|-----------------|--------------|-------------------|-----|
|  <p>[ZP]</p> | 139-2502 | LED-1/18W/2700K | 1190.3 lm    | 18 W              | 80  |
|   | 139-2502 | LED-1/18W/2700K | 1286.6 lm    | 18 W              | 80  |
|   | 139-2496 | LED-1/18W/3000K | 1231.4 lm    | 18 W              | 80  |
|   | 139-2496 | LED-1/18W/3000K | 1330.9 lm    | 18 W              | 80  |
|   | 139-2497 | LED-1/18W/4000K | 1298.1 lm    | 18 W              | 80  |
|   | 139-2497 | LED-1/18W/4000K | 1403 lm      | 18 W              | 80  |
|   | 139-2505 | LED-1/26W/2700K | 1636.7 lm    | 26 W              | 80  |
|   | 139-2505 | LED-1/26W/2700K | 1769 lm      | 26 W              | 80  |
|   | 139-2477 | LED-1/26W/3000K | 1690.6 lm    | 26 W              | 80  |
|   | 139-2477 | LED-1/26W/3000K | 1827.3 lm    | 26 W              | 80  |
|   | 139-2478 | LED-1/26W/4000K | 1780.3 lm    | 26 W              | 80  |
|   | 139-2478 | LED-1/26W/4000K | 1924.3 lm    | 26 W              | 80  |