

Description

IP66, Class III. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One factory installed flange plug M8 x 1.5. Cable length 4 ft. Remote driver in separate driver box (constant current), prewired; to be ordered separately. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board. Tunable White technology. DMX interface.

Maximum one internal optical accessory possible, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK07			




Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	120-277V DMX
Surge protection	6/6 kV (optional SP10)
Energy efficiency	E (Light source)




Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	0.194 ft ²
Lifetime	Ta=25°/Ta=40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [W] bi-symmetric, wide beam	2200-6000K	11 W
 [M] symmetric, medium beam		
 [N] bi-symmetric, narrow beam		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[M] symmetric, medium beam</p>	139-2418_us	LED-3/11W/2200-6000K	963.4 lm	11 W	80
 <p>[N] bi-symmetric, narrow beam</p>	139-2419_us	LED-3/11W/2200-6000K	980.7 lm	11 W	80
 <p>[W] bi-symmetric, wide beam</p>	139-2417_us	LED-3/11W/2200-6000K	953.5 lm	11 W	80