

### Description

Tunable white projector. IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through-wiring on request.

Integral EC electronic converter in thermally-separated compartment. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board with Tunable White Technology.

DALI interface. For other control interface options to suit specific project requirements, contact WE-EF.

## Specifications

### Material description

|                    |                                |                                  |                                   |                                 |
|--------------------|--------------------------------|----------------------------------|-----------------------------------|---------------------------------|
| Colours            | <b>RAL9004</b><br>Signal black | <b>RAL9007</b><br>Grey aluminium | <b>RAL7016</b><br>Anthracite grey | <b>RAL9016</b><br>Traffic white |
| Ingress protection | IP66                           |                                  |                                   |                                 |
| Impact resistance  | IK07                           |                                  |                                   |                                 |

### Electrical description

|                   |                        |
|-------------------|------------------------|
| Power supply      | 220-240V / 50-60 Hz    |
| Driver / Ballast  | DALI                   |
| Surge protection  | 6/6 kV (optional SP10) |
| Energy efficiency | E (Light source)       |

### Additional information

|          |                        |
|----------|------------------------|
| Lifetime | Ta=25° L90B10 > 90000h |
|----------|------------------------|

**Options**

**Light distribution    Colour temperature    Nominal Watt**



[B]

2200-6000K

11 W






[M]



[E]

### Configurations

| Light distribution   | Part ID  | Light source         | Rated lumens | Rated input power | CRI |
|--|----------|----------------------|--------------|-------------------|-----|
|  <p>[B]</p>  | 139-2417 | LED-3/11W/2200-6000K | 953.5 lm     | 11 W              | 80  |
|  <p>[E]</p>  | 139-2419 | LED-3/11W/2200-6000K | 980.7 lm     | 11 W              | 80  |
|  <p>[M]</p> | 139-2418 | LED-3/11W/2200-6000K | 963.4 lm     | 11 W              | 80  |