

**Description**

IP66, Class III. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One factory installed flange plug M8 x 1.5. Cable length 4 ft. Remote driver in separate driver box (constant current), prewired; to be ordered separately. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board. Tunable White technology. DMX interface.

Maximum one internal optical accessory possible, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)  
+ XXX-XXXX (Accessory 1)

**Specifications**

**Material description**

Colors	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown
Ingress protection	IP66			
Impact resistance	IK07			

**Electrical description**

Power supply	220-240V / 50-60 Hz
Driver / Ballast	120-277V DMX
Surge protection	6/6 kV (optional SP10)
Energy efficiency	E (Light source)

**Additional information**

Diameter (inches)	5.90
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	0.194 ft <sup>2</sup>
Lifetime	Ta=25°/Ta=40° L90B10 > 90000h

**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**



[B]

2200-6000K

11 W






[M]



[E]

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[B]</p>	139-2417	LED-3/11W/2200-6000K	953.5 lm	11 W	80
 <p>[E]</p>	139-2419	LED-3/11W/2200-6000K	980.7 lm	11 W	80
 <p>[M]</p>	139-2418	LED-3/11W/2200-6000K	963.4 lm	11 W	80