

**Description**

Tunable White Profile Projector [ZP] for zoom spot. Spherical and aspherical, double flat convex lens system.

IP66, Class I. IK05. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory installed LED circuit board. Tunable White technology. DMX interface.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)  
+ XXX-XXXX (Accessory 1)

**Specifications**

**Material description**

Colors	<b>RAL9004</b> Signal black	<b>RAL9007</b> Grey aluminium	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown
Ingress protection	IP66			
Impact resistance	IK05			

**Electrical description**

Power supply	220-240V / 50-60 Hz
Driver / Ballast	DMX (separate gearbox)
Surge protection	6/6 kV (optional SP10 in separate gearbox, large)
Energy efficiency	E (Light source)

**Additional information**

Diameter (inches)	5.90
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L70B50 > 50000h

**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**




[ZP]

2200-6000K

10 W

**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	139-2492	LED-1/10W/2200-6000K	343.1 lm	10 W	80
	139-2492	LED-1/10W/2200-6000K	514.9 lm	10 W	80

[ZP]