

Description

RGBW/RGBA Colour Changer. IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable glands for improved wiring flexibility. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. DMX interface. M20 cable gland for network- and DMX-connection, WE-EF recommend a multi core cable for DMX & Power "Power PUR-SR 3x1,5 + DMX".

Specifications

Material description

Colours	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="background-color: black; color: white; padding: 5px 10px; border: 1px solid black;">RAL9004</div> <div style="background-color: #cccccc; padding: 5px 10px; border: 1px solid black;">RAL9006</div> <div style="background-color: #999999; padding: 5px 10px; border: 1px solid black;">RAL9007</div> </div> <div style="display: flex; justify-content: space-around; margin-top: 5px;"> Signal black White aluminium Grey aluminium </div>
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE+Primer

Electrical description

Power supply	230V / 50 Hz
Surge protection	1/2 kV (optional SP10)
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options

Light distribution Colour temperature Nominal Watt



[B]

RGBW

24 W






[M]

RGBA



[E]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	139-2146	LED-6/24W/RGBA	1528.3 lm	24 W	80
	139-2038	LED-6/24W/RGBW	2170.6 lm	24 W	80
[B]					
	139-2148	LED-6/24W/RGBA	1669.5 lm	24 W	80
	139-2148	LED-6/24W/RGBA	1669.5 lm	24 W	80
	139-2040	LED-6/24W/RGBW	2371.2 lm	24 W	80
	139-2040	LED-6/24W/RGBW	2371.2 lm	24 W	80
[E]					
	139-2147	LED-6/24W/RGBA	1594.9 lm	24 W	80
	139-2147	LED-6/24W/RGBA	1594.9 lm	24 W	80
	139-2039	LED-6/24W/RGBW	2265.3 lm	24 W	80
	139-2039	LED-6/24W/RGBW	2265.3 lm	24 W	80
[M]					