

Description

Tunable White. IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through-wiring on request. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board with Tunable White Technology. DALI Interface.

Specifications

Material description

| | | | | |
|--------------------|----------------|-----------------|----------------|-----------------|
| Colours | RAL9004 | RAL9006 | RAL9007 | RAL7016 |
| | Signal black | White aluminium | Grey aluminium | Anthracite grey |
| | RAL9016 | | | |
| | Traffic white | | | |
| Ingress protection | IP66 | | | |
| Impact resistance | IK07 | | | |

Electrical description

| | |
|-------------------|---------------------|
| Power supply | 220-240V / 50-60 Hz |
| Energy efficiency | E (Lichtquelle) |

Additional information

| | |
|----------|------------------------|
| Lifetime | Ta=25° L90B10 > 90000h |
|----------|------------------------|

Options**Light distribution****Colour temperature****Nominal Watt**

[B] symmetric, wide beam

2200-6000K

22 W






[E] symmetric, narrow beam



[M] symmetric, medium beam

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|---|----------|----------------------|--------------|-------------------|-----|
|  <p>[B] symmetric, wide beam</p> | 139-2041 | LED-6/22W/2200-6000K | 2043.5 lm | 22 W | 80 |
|  <p>[E] symmetric, narrow beam</p> | 139-2043 | LED-6/22W/2200-6000K | 2080.3 lm | 22 W | 80 |
|  <p>[M] symmetric, medium beam</p> | 139-2042 | LED-6/22W/2200-6000K | 2027.4 lm | 22 W | 80 |