

**Description**

Tunable White. IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through-wiring on request. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board with Tunable White Technology. DALI Interface.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Power supply	220-240V / 50-60 Hz
Energy efficiency	E (Lichtquelle)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**

**Light distribution    Colour temperature    Nominal Watt**



[B]

2200-6000K

22 W






[E]



[M]

### Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	139-2041	LED-6/22W/2200-6000K	2043.5 lm	22 W	80
[B]					
	139-2043	LED-6/22W/2200-6000K	2080.3 lm	22 W	80
	139-2043	LED-6/22W/2200-6000K	2080.3 lm	22 W	80
[E]					
	139-2042	LED-6/22W/2200-6000K	2027.4 lm	22 W	80
[M]					