

Description

Tunable white projector. IP66. Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Two cable glands.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with Tunable White Technology.

DALI Interface . For other control interface options to suit specific project requirements, contact WE-EF.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK07			

Electrical description

Power supply	220-240V / 50-60 Hz
Energy efficiency	E (Lichtquelle)

Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution	Colour temperature	Nominal Watt
--------------------	--------------------	--------------



[B]

2200-6000K

22 W






[E]



[M]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	139-2041	LED-6/22W/2200-6000K	2043.5 lm	22 W	80
[B]					
	139-2043	LED-6/22W/2200-6000K	2080.3 lm	22 W	80
	139-2043	LED-6/22W/2200-6000K	2080.3 lm	22 W	80
[E]					
	139-2042	LED-6/22W/2200-6000K	2027.4 lm	22 W	80
[M]					