

Description

RGBW/RGBA Colour Changer. IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable glands for improved wiring flexibility. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. DMX interface. M20 cable gland for network- and DMX-connection, WE-EF recommend a multi core cable for DMX & Power "Power PUR-SR 3x1,5 + DMX".

Separation of DMX and Power supply on request.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy		
Lens	Safety glass lens		
Colours	RAL9004	RAL9006	RAL9007
	Signal black	White aluminium	Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP66		
Impact resistance	IK07		
Corrosion resistance	5CE+Primer		

Electrical description

Power supply	230V / 50 Hz
Surge protection	1/2 kV (optional SP10)
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options

Light distribution Colour temperature Nominal Watt



[B]

4000K+RGBW

48 W

42 W



[M]

RGBA







[EES]



[E]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	139-1929	LED-12/48W/4000K+RGBW	3377.9 lm	48 W	80
	139-2137	LED-12/48W/RGBA	3026.9 lm	48 W	80
[B]					
	139-1914	LED-12/48W/4000K+RGBW	3559.8 lm	48 W	80
	139-1914	LED-12/48W/4000K+RGBW	3559.8 lm	48 W	80
	139-2138	LED-12/48W/RGBA	3189.9 lm	48 W	80
	139-2138	LED-12/48W/RGBA	3189.9 lm	48 W	80
[E]					
	139-2420	LED-4x6/42W/4000K+RGBW	2573.3 lm	42 W	80
	139-2422	LED-4x6/42W/RGBA	2547.3 lm	42 W	80
[EES]					
	139-1913	LED-12/48W/4000K+RGBW	3629.1 lm	48 W	80
	139-1913	LED-12/48W/4000K+RGBW	3629.1 lm	48 W	80
	139-2139	LED-12/48W/RGBA	3252.1 lm	48 W	80
	139-2139	LED-12/48W/RGBA	3252.1 lm	48 W	80
[M]					