

Description

IP66, Class I. Class II on request.

IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through wiring on request. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 1-10V, DALI Interface or Eco Step Dim® on request. Maximum one internal optical accessory possible.

Optional 2200 K version up to max. 1050mA available, except version [EES]. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Safety glass lens			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey
	RAL9007 Grey aluminium			
Gasket	Silicone CCG® Controlled Compression Gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			









Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)




Additional information



Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

Options

Light distribution	Colour temperature	Nominal Watt
 [M]	 3000K	24 W
		36 W
 [E]	 4000K	52 W
		48 W
		72 W
 [EE]	 2700K	
 [B]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[B]</p>	139-2241	LED-12/24W/2700K	2784.4 lm	24 W	80
	139-1907	LED-12/24W/3000K	2990.7 lm	24 W	80
	139-1908	LED-12/24W/4000K	3197 lm	24 W	80
	139-2239	LED-12/36W/2700K	4228.2 lm	36 W	80
	139-1909	LED-12/36W/3000K	4434.5 lm	36 W	80
	139-1910	LED-12/36W/4000K	4640.7 lm	36 W	80
	139-2226	LED-12/52W/2700K	5181.4 lm	52 W	80
	139-1911	LED-12/52W/3000K	5480.4 lm	52 W	80
	139-1912	LED-12/52W/4000K	5729.5 lm	52 W	80
	 <p>[E]</p>	139-2242	LED-12/24W/2700K	2761 lm	24 W
139-1832		LED-12/24W/3000K	2965.5 lm	24 W	80
139-1833		LED-12/24W/4000K	3170 lm	24 W	80
139-2079		LED-12/36W/2700K	4192.6 lm	36 W	80
139-2079		LED-12/36W/2700K	4192.6 lm	36 W	80
139-1838		LED-12/36W/3000K	4397.1 lm	36 W	80
139-1839		LED-12/36W/4000K	4601.7 lm	36 W	80
139-2214		LED-12/52W/2700K	5117 lm	52 W	80
139-1844		LED-12/52W/3000K	5412.2 lm	52 W	80
139-1845		LED-12/52W/4000K	5658.2 lm	52 W	80
139-2263		LED-12/24W/2700K	2905.3 lm	24 W	80
139-2263		LED-12/24W/2700K	2905.3 lm	24 W	80
 <p>[EE]</p>		139-1834	LED-12/24W/3000K	3120.5 lm	24 W
	139-1834	LED-12/24W/3000K	3120.5 lm	24 W	80
	139-1835	LED-12/24W/4000K	3335.7 lm	24 W	80
	139-1835	LED-12/24W/4000K	3335.7 lm	24 W	80
	139-2077	LED-12/36W/2700K	4411.8 lm	36 W	80
	139-2077	LED-12/36W/2700K	4411.8 lm	36 W	80
	139-1840	LED-12/36W/3000K	4627 lm	36 W	80
	139-1840	LED-12/36W/3000K	4627 lm	36 W	80
	139-1841	LED-12/36W/4000K	4842.2 lm	36 W	80
	139-1841	LED-12/36W/4000K	4842.2 lm	36 W	80
	139-2191	LED-12/52W/2700K	5483.7 lm	52 W	80
	139-2191	LED-12/52W/2700K	5483.7 lm	52 W	80
	139-1846	LED-12/52W/3000K	5800 lm	52 W	80

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [EES]	139-1846	LED-12/52W/3000K	5800 lm	52 W	80
	139-1847	LED-12/52W/4000K	6063.7 lm	52 W	80
	139-1847	LED-12/52W/4000K	6063.7 lm	52 W	80
	139-3125	LED-24/36W/2700K	3249.5 lm	36 W	80
	139-3126	LED-24/36W/3000K	3473.6 lm	36 W	80
	139-3127	LED-24/36W/4000K	3473.6 lm	36 W	80
	139-3129	LED-24/48W/2700K	4257.9 lm	48 W	80
	139-3130	LED-24/48W/3000K	4594.1 lm	48 W	80
	139-3131	LED-24/48W/4000K	4594.1 lm	48 W	80
	139-3133	LED-24/72W/2700K	5714.6 lm	72 W	80
	139-3134	LED-24/72W/3000K	6162.8 lm	72 W	80
	139-3135	LED-24/72W/4000K	6162.8 lm	72 W	80
	 [M]	139-2151	LED-12/24W/2700K	2934.9 lm	24 W
139-2151		LED-12/24W/2700K	2934.9 lm	24 W	80
139-1830		LED-12/24W/3000K	3152.3 lm	24 W	80
139-1830		LED-12/24W/3000K	3152.3 lm	24 W	80
139-1831		LED-12/24W/4000K	3369.7 lm	24 W	80
139-1831		LED-12/24W/4000K	3369.7 lm	24 W	80
139-2240		LED-12/36W/2700K	4456.7 lm	36 W	80
139-2240		LED-12/36W/2700K	4456.7 lm	36 W	80
139-1836		LED-12/36W/3000K	4674.1 lm	36 W	80
139-1836		LED-12/36W/3000K	4674.1 lm	36 W	80
139-1837		LED-12/36W/4000K	4891.5 lm	36 W	80
139-1837		LED-12/36W/4000K	4891.5 lm	36 W	80
139-2108		LED-12/52W/2700K	5435.2 lm	52 W	80
139-2108		LED-12/52W/2700K	5435.2 lm	52 W	80
139-1842		LED-12/52W/3000K	5748.8 lm	52 W	80
139-1842		LED-12/52W/3000K	5748.8 lm	52 W	80
139-1843		LED-12/52W/4000K	6010.1 lm	52 W	80
139-1843		LED-12/52W/4000K	6010.1 lm	52 W	80