

**Description**

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.

For 2200 K version available on request, except [EES] distribution.

## Specifications

### Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Safety glass lens			
Colours	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL7016</b>	<b>RAL9007</b>
	Signal black	Traffic white	Anthracite grey	Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK07			
Corrosion resistance	5CE			

### Electrical description







Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)

### Additional information




Windage	0.116 m <sup>2</sup>
Lifetime	Ta=25° L90B10 > 90000h



**Options**

**Light distribution    Colour temperature    Nominal Watt**

	[M]		3000K	72 W
	[E]		4000K	108 W
	[EE]	2700K	155 W	
	[B]		144 W	
	[EES]			

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 <p>[B]</p>	139-2257	LED-36/72W/2700K	8353.3 lm	72 W	80
	139-1955	LED-36/72W/3000K	8972.1 lm	72 W	80
	139-1956	LED-36/72W/4000K	9590.9 lm	72 W	80
	139-2254	LED-36/108W/2700K	12684.7 lm	108 W	80
	139-1959	LED-36/108W/3000K	13303.5 lm	108 W	80
	139-1960	LED-36/108W/4000K	13922.2 lm	108 W	80
	139-2230	LED-36/155W/2700K	15544.3 lm	155 W	80
	139-1963	LED-36/155W/3000K	16441.1 lm	155 W	80
	139-1964	LED-36/155W/4000K	17188.5 lm	155 W	80
	 <p>[E]</p>	139-2259	LED-36/72W/2700K	8283 lm	72 W
139-1808		LED-36/72W/3000K	8896.5 lm	72 W	80
139-1809		LED-36/72W/4000K	9510.1 lm	72 W	80
139-2256		LED-36/108W/2700K	12577.9 lm	108 W	80
139-1793		LED-36/108W/3000K	13191.4 lm	108 W	80
139-1794		LED-36/108W/4000K	13805 lm	108 W	80
139-2231		LED-36/155W/2700K	15351 lm	155 W	80
139-1799		LED-36/155W/3000K	16236.7 lm	155 W	80
139-1800		LED-36/155W/4000K	16974.7 lm	155 W	80
 <p>[EE]</p>		139-2267	LED-36/72W/2700K	8715.9 lm	72 W
	139-2267	LED-36/72W/2700K	8715.9 lm	72 W	80
	139-1810	LED-36/72W/3000K	9361.6 lm	72 W	80
	139-1810	LED-36/72W/3000K	9361.6 lm	72 W	80
	139-1811	LED-36/72W/4000K	10007.2 lm	72 W	80
	139-1811	LED-36/72W/4000K	10007.2 lm	72 W	80
	139-2274	LED-36/108W/2700K	13235.3 lm	108 W	80
	139-2274	LED-36/108W/2700K	13235.3 lm	108 W	80
	139-1795	LED-36/108W/3000K	13881 lm	108 W	80
	139-1795	LED-36/108W/3000K	13881 lm	108 W	80
	139-1796	LED-36/108W/4000K	14526.6 lm	108 W	80
	139-1796	LED-36/108W/4000K	14526.6 lm	108 W	80
	139-2281	LED-36/155W/2700K	16451 lm	155 W	80
	139-2281	LED-36/155W/2700K	16451 lm	155 W	80
	139-1801	LED-36/155W/3000K	17400.1 lm	155 W	80
	139-1801	LED-36/155W/3000K	17400.1 lm	155 W	80

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	139-1802	LED-36/155W/4000K	18191.1 lm	155 W	80
	139-1802	LED-36/155W/4000K	18191.1 lm	155 W	80
 [EES]	139-3149	LED-72/108W/2700K	9748.4 lm	108 W	80
	139-3150	LED-72/108W/3000K	10420.7 lm	108 W	80
	139-3151	LED-72/108W/4000K	10420.7 lm	108 W	80
	139-3153	LED-72/144W/2700K	12773.8 lm	144 W	80
	139-3154	LED-72/144W/3000K	13782.2 lm	144 W	80
	139-3155	LED-72/144W/4000K	13782.2 lm	144 W	80
	 [M]	139-2258	LED-36/72W/2700K	8804.8 lm	72 W
139-2258		LED-36/72W/2700K	8804.8 lm	72 W	80
139-1806		LED-36/72W/3000K	9457 lm	72 W	80
139-1806		LED-36/72W/3000K	9457 lm	72 W	80
139-1807		LED-36/72W/4000K	10109.2 lm	72 W	80
139-1807		LED-36/72W/4000K	10109.2 lm	72 W	80
139-2255		LED-36/108W/2700K	13370.2 lm	108 W	80
139-2255		LED-36/108W/2700K	13370.2 lm	108 W	80
139-1791		LED-36/108W/3000K	14022.4 lm	108 W	80
139-1791		LED-36/108W/3000K	14022.4 lm	108 W	80
139-1792		LED-36/108W/4000K	14674.6 lm	108 W	80
139-1792		LED-36/108W/4000K	14674.6 lm	108 W	80
139-2175		LED-36/155W/2700K	16305.6 lm	155 W	80
139-2175		LED-36/155W/2700K	16305.6 lm	155 W	80
139-1797		LED-36/155W/3000K	17246.3 lm	155 W	80
139-1797		LED-36/155W/3000K	17246.3 lm	155 W	80
139-1798		LED-36/155W/4000K	18030.3 lm	155 W	80
139-1798		LED-36/155W/4000K	18030.3 lm	155 W	80