

Description

Tunable White. IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through-wiring on request. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board with Tunable White Technology. DALI Interface.

Specifications

Material description

| | | | | |
|--------------------|----------------|-----------------|----------------|-----------------|
| Colours | RAL9004 | RAL9006 | RAL9007 | RAL7016 |
| | Signal black | White aluminium | Grey aluminium | Anthracite grey |
| | RAL9016 | | | |
| | Traffic white | | | |
| Ingress protection | IP66 | | | |
| Impact resistance | IK07 | | | |

Electrical description

| | |
|-------------------|------------------------|
| Power supply | 220-240V / 50-60 Hz |
| Surge protection | 1/2 kV (optional SP10) |
| Energy efficiency | E (Light source) |

Additional information

| | |
|----------|------------------------|
| Lifetime | Ta=25° L90B10 > 90000h |
|----------|------------------------|

Options

Light distribution Colour temperature Nominal Watt



[B]

2200-6000K

132 W

72 W



[M]

2700-6000K







[E]



[EES]

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|--|----------|------------------------|--------------|-------------------|-----|
|  [B] | 139-2050 | LED-36/132W/2200-6000K | 11447.3 lm | 132 W | 80 |
| | 139-2052 | LED-36/132W/2200-6000K | 12386.8 lm | 132 W | 80 |
|  [E] | 139-2052 | LED-36/132W/2200-6000K | 12386.8 lm | 132 W | 80 |
| | 139-2052 | LED-36/132W/2200-6000K | 12386.8 lm | 132 W | 80 |
|  [EES] | 139-2431 | LED-72/72W/2700-6000K | 6386.9 lm | 72 W | 80 |
| | 139-2431 | LED-72/72W/2700-6000K | 6386.9 lm | 72 W | 80 |
|  [M] | 139-2051 | LED-36/132W/2200-6000K | 12174 lm | 132 W | 80 |
| | 139-2051 | LED-36/132W/2200-6000K | 12174 lm | 132 W | 80 |