

### Description

IP66. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Two cable entries.

Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

Mains voltage versions, ON-OFF Class I. Integral EC electronic converter.

Knuckle permits 340° rotation, forward tilt 73° and backward tilt 90°.

Optical accessories are factory-installed. To be specified at time of ordering.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9007</b>	<b>RAL7016</b>	<b>RAL9016</b>
	Signal black	Grey aluminium	Anthracite grey	Traffic white
	<b>RAL9006</b>			
	White aluminium			
Ingress protection	IP66			
Impact resistance	IK07			

### Electrical description

Energy efficiency	D-E (Light source)
-------------------	--------------------

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**

**Light distribution    Colour temperature    Nominal Watt**



[B]



2700K

4 W




[M]



3000K



[E]



4000K








[EE]



[EES]

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	145-7204	LED-1/4W/2700K	379.1 lm	4 W	80
	145-7205	LED-1/4W/3000K	379.1 lm	4 W	80
	145-7206	LED-1/4W/4000K	410.1 lm	4 W	80
[B]					
	145-7246	LED-1/4W/2700K	415.2 lm	4 W	80
	145-7247	LED-1/4W/3000K	415.2 lm	4 W	80
	145-7248	LED-1/4W/4000K	449.1 lm	4 W	80
[E]					
	145-7210	LED-1/4W/2700K	415.5 lm	4 W	80
	145-7210	LED-1/4W/2700K	415.5 lm	4 W	80
	145-7211	LED-1/4W/3000K	415.5 lm	4 W	80
	145-7211	LED-1/4W/3000K	415.5 lm	4 W	80
	145-7212	LED-1/4W/4000K	449.5 lm	4 W	80
	145-7212	LED-1/4W/4000K	449.5 lm	4 W	80
[EE]					
	145-7213	LED-1/4W/2700K	382.2 lm	4 W	80
	145-7213	LED-1/4W/2700K	382.2 lm	4 W	80
	145-7214	LED-1/4W/3000K	382.2 lm	4 W	80
	145-7214	LED-1/4W/3000K	382.2 lm	4 W	80
	145-7215	LED-1/4W/4000K	411.6 lm	4 W	80
	145-7215	LED-1/4W/4000K	411.6 lm	4 W	80
[EES]					
	145-7207	LED-1/4W/2700K	398.4 lm	4 W	80
	145-7207	LED-1/4W/2700K	398.4 lm	4 W	80
	145-7208	LED-1/4W/3000K	398.4 lm	4 W	80
	145-7208	LED-1/4W/3000K	398.4 lm	4 W	80
	145-7209	LED-1/4W/4000K	431 lm	4 W	80
	145-7209	LED-1/4W/4000K	431 lm	4 W	80
[M]					