

Description

IP66. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

4W / 120V mains voltage version, ON-OFF Class I.

Including 1.3 ft of flexible cable enclosed in a stainless conduit, in-line connector and mounting clamp for installation to RAIL66 mounting system.

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white
Ingress protection	IP66		
Impact resistance	IK07		









Electrical description

Energy efficiency	D-E (Light source)
-------------------	--------------------






Additional information

Diameter (inches)	2.30
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	0.107 ft ²
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B]	 2700K	4 W
 [M]	 3000K	
 [E]	 4000K	
 [EE]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	145-7216	LED-1/4W/2700K	379.1 lm	4 W	80
	145-7217	LED-1/4W/3000K	379.1 lm	4 W	80
	145-7218	LED-1/4W/4000K	410.1 lm	4 W	80
[B]	<hr/>				
	145-7249	LED-1/4W/2700K	415.2 lm	4 W	80
	145-7250	LED-1/4W/3000K	415.2 lm	4 W	80
	145-7251	LED-1/4W/4000K	449.1 lm	4 W	80
[E]	<hr/>				
	145-7222	LED-1/4W/2700K	415.5 lm	4 W	80
	145-7222	LED-1/4W/2700K	415.5 lm	4 W	80
	145-7223	LED-1/4W/3000K	415.5 lm	4 W	80
	145-7223	LED-1/4W/3000K	415.5 lm	4 W	80
	145-7224	LED-1/4W/4000K	449.5 lm	4 W	80
	145-7224	LED-1/4W/4000K	449.5 lm	4 W	80
[EE]	<hr/>				
	145-7225	LED-1/4W/2700K	382.2 lm	4 W	80
	145-7225	LED-1/4W/2700K	382.2 lm	4 W	80
	145-7226	LED-1/4W/3000K	382.2 lm	4 W	80
	145-7226	LED-1/4W/3000K	382.2 lm	4 W	80
	145-7227	LED-1/4W/4000K	411.6 lm	4 W	80
	145-7227	LED-1/4W/4000K	411.6 lm	4 W	80
[EES]	<hr/>				
	145-7219	LED-1/4W/2700K	398.4 lm	4 W	80
	145-7219	LED-1/4W/2700K	398.4 lm	4 W	80
	145-7220	LED-1/4W/3000K	398.4 lm	4 W	80
	145-7220	LED-1/4W/3000K	398.4 lm	4 W	80
	145-7221	LED-1/4W/4000K	431 lm	4 W	80
	145-7221	LED-1/4W/4000K	431 lm	4 W	80
[M]	<hr/>				