

### Description

IP66. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

Mains voltage versions only, ON-OFF Class I. 1-10 V analogue dimming or DALI interface available on request (converter in thermally-separated compartment); refer to accessory listings.

Optical accessories are factory-installed. To be specified at time of ordering.

Including terminal box, for mounting on  $\varnothing$  48-60 mm pipes or space frames.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9007</b>	<b>RAL7016</b>	<b>RAL9016</b>
	Signal black	Grey aluminium	Anthracite grey	Traffic white
	<b>RAL9006</b>			
	White aluminium			
Ingress protection	IP66			
Impact resistance	IK07			









### Electrical description

Energy efficiency	D-E (Light source)
-------------------	--------------------






### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**

Light distribution	Colour temperature	Nominal Watt
 [B]	 2700K	4 W
 [M]	 3000K	
 [E]	 4000K	
 [EE]		
 [EES]		

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	145-7270	LED-1/4W/2700K	379.1 lm	4 W	80
	145-7271	LED-1/4W/3000K	379.1 lm	4 W	80
	145-7272	LED-1/4W/4000K	410.1 lm	4 W	80
[B]					
	145-7276	LED-1/4W/2700K	415.2 lm	4 W	80
	145-7277	LED-1/4W/3000K	415.2 lm	4 W	80
	145-7278	LED-1/4W/4000K	449.1 lm	4 W	80
[E]					
	145-7279	LED-1/4W/2700K	415.5 lm	4 W	80
	145-7279	LED-1/4W/2700K	415.5 lm	4 W	80
	145-7280	LED-1/4W/3000K	415.5 lm	4 W	80
	145-7280	LED-1/4W/3000K	415.5 lm	4 W	80
	145-7281	LED-1/4W/4000K	449.5 lm	4 W	80
[EE]					
	145-7282	LED-1/4W/2700K	382.2 lm	4 W	80
	145-7282	LED-1/4W/2700K	382.2 lm	4 W	80
	145-7283	LED-1/4W/3000K	382.2 lm	4 W	80
	145-7283	LED-1/4W/3000K	382.2 lm	4 W	80
	145-7284	LED-1/4W/4000K	411.6 lm	4 W	80
	145-7284	LED-1/4W/4000K	411.6 lm	4 W	80
[EES]					
	145-7273	LED-1/4W/2700K	398.4 lm	4 W	80
	145-7273	LED-1/4W/2700K	398.4 lm	4 W	80
	145-7274	LED-1/4W/3000K	398.4 lm	4 W	80
	145-7274	LED-1/4W/3000K	398.4 lm	4 W	80
	145-7275	LED-1/4W/4000K	431 lm	4 W	80
[M]					
	145-7275	LED-1/4W/4000K	431 lm	4 W	80