

Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Including 5 ft of flexible PVC free cable.

Optical accessories are factory-installed. To be specified at time of ordering.

6-12W / 120V / 0-10V Dimming.
6W / 24V DC / 0-10V Dimming. (available upon request)

Contact the factory for 277V/347V options.

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Ingress protection	IP66			
Impact resistance	IK08			








Electrical description

Power supply	120-277VAC/50-60 Hz (24V DC available upon request)
Driver / Ballast	Integral [ECG] electronic driver 120V-277V. (24VDC low voltage, available upon request)
Energy efficiency	0-10V as standard



Additional information



Diameter (inches)	3.40
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	0.215 ft ²
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [B]	 2700K	6 W 9 W 12 W
 [M]	 3000K	
[]	 4000K	
 [EE]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	
[]	145-7615	LED-3/6W/4000K	646.6 lm	6 W	80	
	145-7615	LED-3/6W/4000K	646.6 lm	6 W	80	
 [B]	145-7600	LED-3/6W/2700K	595.4 lm	6 W	80	
	145-7603	LED-3/6W/3000K	595.4 lm	6 W	80	
	145-7606	LED-3/6W/4000K	641.2 lm	6 W	80	
	145-7601	LED-3/9W/2700K	835.8 lm	9 W	80	
	145-7604	LED-3/9W/3000K	835.8 lm	9 W	80	
	145-7607	LED-3/9W/4000K	893.1 lm	9 W	80	
	145-7602	LED-3/12W/2700K	1122.1 lm	12 W	80	
	145-7605	LED-3/12W/3000K	1122.1 lm	12 W	80	
	145-7608	LED-3/12W/4000K	1213.7 lm	12 W	80	
	 [EE]	145-7618	LED-3/6W/2700K	605.2 lm	6 W	80
		145-7618	LED-3/6W/2700K	605.2 lm	6 W	80
		145-7621	LED-3/6W/3000K	605.2 lm	6 W	80
145-7621		LED-3/6W/3000K	605.2 lm	6 W	80	
145-7624		LED-3/6W/4000K	651.7 lm	6 W	80	
145-7624		LED-3/6W/4000K	651.7 lm	6 W	80	
145-7619		LED-3/9W/2700K	849.6 lm	9 W	80	
145-7619		LED-3/9W/2700K	849.6 lm	9 W	80	
145-7622		LED-3/9W/3000K	849.6 lm	9 W	80	
145-7622		LED-3/9W/3000K	849.6 lm	9 W	80	
145-7625		LED-3/9W/4000K	907.8 lm	9 W	80	
145-7625		LED-3/9W/4000K	907.8 lm	9 W	80	
145-7620		LED-3/12W/2700K	1140.5 lm	12 W	80	
145-7620		LED-3/12W/2700K	1140.5 lm	12 W	80	
145-7623		LED-3/12W/3000K	1140.5 lm	12 W	80	
145-7623		LED-3/12W/3000K	1140.5 lm	12 W	80	
145-7626		LED-3/12W/4000K	1233.6 lm	12 W	80	
145-7626		LED-3/12W/4000K	1233.6 lm	12 W	80	
145-7627		LED-3/6W/2700K	606.3 lm	6 W	80	
145-7627		LED-3/6W/2700K	606.3 lm	6 W	80	
145-7630		LED-3/6W/3000K	606.3 lm	6 W	80	

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [EES]	145-7630	LED-3/6W/3000K	606.3 lm	6 W	80
	145-7633	LED-3/6W/4000K	656.8 lm	6 W	80
	145-7633	LED-3/6W/4000K	656.8 lm	6 W	80
	145-7628	LED-3/9W/2700K	858.9 lm	9 W	80
	145-7628	LED-3/9W/2700K	858.9 lm	9 W	80
	145-7631	LED-3/9W/3000K	858.9 lm	9 W	80
	145-7631	LED-3/9W/3000K	858.9 lm	9 W	80
	145-7634	LED-3/9W/4000K	922 lm	9 W	80
	145-7634	LED-3/9W/4000K	922 lm	9 W	80
	145-7629	LED-3/12W/2700K	1149.4 lm	12 W	80
	145-7629	LED-3/12W/2700K	1149.4 lm	12 W	80
	145-7632	LED-3/12W/3000K	1149.4 lm	12 W	80
	145-7632	LED-3/12W/3000K	1149.4 lm	12 W	80
	145-7635	LED-3/12W/4000K	1237.8 lm	12 W	80
	145-7635	LED-3/12W/4000K	1237.8 lm	12 W	80
	 [M]	145-7609	LED-3/6W/2700K	600.4 lm	6 W
145-7609		LED-3/6W/2700K	600.4 lm	6 W	80
145-7612		LED-3/6W/3000K	600.4 lm	6 W	80
145-7612		LED-3/6W/3000K	600.4 lm	6 W	80
145-7610		LED-3/9W/2700K	842.9 lm	9 W	80
145-7610		LED-3/9W/2700K	842.9 lm	9 W	80
145-7613		LED-3/9W/3000K	842.9 lm	9 W	80
145-7613		LED-3/9W/3000K	842.9 lm	9 W	80
145-7616		LED-3/9W/4000K	900.6 lm	9 W	80
145-7616		LED-3/9W/4000K	900.6 lm	9 W	80
145-7611		LED-3/12W/2700K	1131.6 lm	12 W	80
145-7611		LED-3/12W/2700K	1131.6 lm	12 W	80
145-7614		LED-3/12W/3000K	1131.6 lm	12 W	80
145-7614		LED-3/12W/3000K	1131.6 lm	12 W	80
145-7617		LED-3/12W/4000K	1224 lm	12 W	80
145-7617		LED-3/12W/4000K	1224 lm	12 W	80