

Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

Mains voltage versions, DALI interface Class I. 1-10 V analogue dimming available on request; refer to accessory listings.

24VDC low voltage versions, 0-10 V analogue dimming (only 9W available) Class III available on request.

Including 0.4 m of flexible cable enclosed in a stainless conduit, in-line connector and mounting clamp for installation to RAIL66 mounting system.

Optical accessories are factory-installed. To be specified at time of ordering.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK08			

Electrical description

Energy efficiency	D-E (Light source)
-------------------	--------------------

Additional information

Listings	Knuckle permits 340° rotation, forward tilt 54° and backward tilt 90°
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution Colour temperature Nominal Watt



[B]



2700K

6 W

9 W

12 W




[M]



3000K



[EE]






4000K



[EES]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	
 <p>[B]</p>	145-7708	LED-3/6W/2700K	595.4 lm	6 W	80	
	145-7711	LED-3/6W/3000K	595.4 lm	6 W	80	
	145-7714	LED-3/6W/4000K	641.2 lm	6 W	80	
	145-7709	LED-3/9W/2700K	835.8 lm	9 W	80	
	145-7712	LED-3/9W/3000K	835.8 lm	9 W	80	
	145-7715	LED-3/9W/4000K	893.1 lm	9 W	80	
	145-7710	LED-3/12W/2700K	1122.1 lm	12 W	80	
	145-7713	LED-3/12W/3000K	1122.1 lm	12 W	80	
	145-7716	LED-3/12W/4000K	1213.7 lm	12 W	80	
	 <p>[EE]</p>	145-7726	LED-3/6W/2700K	605.2 lm	6 W	80
145-7726		LED-3/6W/2700K	605.2 lm	6 W	80	
145-7729		LED-3/6W/3000K	605.2 lm	6 W	80	
145-7729		LED-3/6W/3000K	605.2 lm	6 W	80	
145-7732		LED-3/6W/4000K	651.7 lm	6 W	80	
145-7732		LED-3/6W/4000K	651.7 lm	6 W	80	
145-7727		LED-3/9W/2700K	849.6 lm	9 W	80	
145-7727		LED-3/9W/2700K	849.6 lm	9 W	80	
145-7730		LED-3/9W/3000K	849.6 lm	9 W	80	
145-7730		LED-3/9W/3000K	849.6 lm	9 W	80	
145-7733		LED-3/9W/4000K	907.8 lm	9 W	80	
145-7733		LED-3/9W/4000K	907.8 lm	9 W	80	
145-7728		LED-3/12W/2700K	1140.5 lm	12 W	80	
145-7728		LED-3/12W/2700K	1140.5 lm	12 W	80	
145-7731		LED-3/12W/3000K	1140.5 lm	12 W	80	
145-7731		LED-3/12W/3000K	1140.5 lm	12 W	80	
145-7734		LED-3/12W/4000K	1233.6 lm	12 W	80	
145-7734		LED-3/12W/4000K	1233.6 lm	12 W	80	
 <p>[EES]</p>		145-7735	LED-3/6W/2700K	606.3 lm	6 W	80
		145-7735	LED-3/6W/2700K	606.3 lm	6 W	80
	145-7738	LED-3/6W/3000K	606.3 lm	6 W	80	
	145-7738	LED-3/6W/3000K	606.3 lm	6 W	80	
	145-7741	LED-3/6W/4000K	656.8 lm	6 W	80	
	145-7741	LED-3/6W/4000K	656.8 lm	6 W	80	
	145-7736	LED-3/9W/2700K	858.9 lm	9 W	80	

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	145-7736	LED-3/9W/2700K	858.9 lm	9 W	80
	145-7739	LED-3/9W/3000K	858.9 lm	9 W	80
	145-7739	LED-3/9W/3000K	858.9 lm	9 W	80
	145-7742	LED-3/9W/4000K	922 lm	9 W	80
	145-7742	LED-3/9W/4000K	922 lm	9 W	80
	145-7737	LED-3/12W/2700K	1149.4 lm	12 W	80
	145-7737	LED-3/12W/2700K	1149.4 lm	12 W	80
	145-7740	LED-3/12W/3000K	1149.4 lm	12 W	80
	145-7740	LED-3/12W/3000K	1149.4 lm	12 W	80
	145-7743	LED-3/12W/4000K	1237.8 lm	12 W	80
	145-7743	LED-3/12W/4000K	1237.8 lm	12 W	80
	145-7717	LED-3/6W/2700K	600.4 lm	6 W	80
	145-7717	LED-3/6W/2700K	600.4 lm	6 W	80
	145-7720	LED-3/6W/3000K	600.4 lm	6 W	80
	145-7720	LED-3/6W/3000K	600.4 lm	6 W	80
	145-7723	LED-3/6W/4000K	646.6 lm	6 W	80
	145-7723	LED-3/6W/4000K	646.6 lm	6 W	80
	145-7718	LED-3/9W/2700K	842.9 lm	9 W	80
	145-7718	LED-3/9W/2700K	842.9 lm	9 W	80
	145-7721	LED-3/9W/3000K	842.9 lm	9 W	80
	145-7721	LED-3/9W/3000K	842.9 lm	9 W	80
	145-7724	LED-3/9W/4000K	900.6 lm	9 W	80
	145-7724	LED-3/9W/4000K	900.6 lm	9 W	80
	145-7719	LED-3/12W/2700K	1131.6 lm	12 W	80
	145-7719	LED-3/12W/2700K	1131.6 lm	12 W	80
	145-7722	LED-3/12W/3000K	1131.6 lm	12 W	80
	145-7722	LED-3/12W/3000K	1131.6 lm	12 W	80
	145-7725	LED-3/12W/4000K	1224 lm	12 W	80
	145-7725	LED-3/12W/4000K	1224 lm	12 W	80



[M]