

Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Including 1.5 m of flexible PVC free cable.

Mains voltage versions, DALI interface Class I. 1-10 V analogue dimming available on request; refer to accessory listings.

DALI interface Class II available on request; refer to accessory listings.

24VDC low voltage versions, 0-10 V analogue dimming or DALI interface Class III available on request.

Remote 24VDC power supply to be ordered separately.

Optical accessories are factory-installed. To be specified at time of ordering.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK08			







Electrical description

Driver / Ballast	DALI interface
Energy efficiency	C-D (Light source)




Additional information

Listings	Knuckle permits 340° rotation, forward tilt 54° and backward tilt 90°
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution	Colour temperature	Nominal Watt
 [B]	 2700K	12 W
		18 W
	 [M]	 3000K
 [EE]		
 [EES]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	
 <p>[B]</p>	145-9943	LED-6/12W/2700K	887.8 lm	12 W	80	
	145-9945	LED-6/12W/3000K	953.5 lm	12 W	80	
	145-9947	LED-6/12W/4000K	1019.3 lm	12 W	80	
	145-9944	LED-6/18W/2700K	1233 lm	18 W	80	
	145-9946	LED-6/18W/3000K	1331.7 lm	18 W	80	
	145-9948	LED-6/18W/4000K	1413.9 lm	18 W	80	
	145-7320	LED-6/26W/2700K	1665.8 lm	26 W	80	
	145-7321	LED-6/26W/3000K	1761.9 lm	26 W	80	
	145-7322	LED-6/26W/4000K	1842 lm	26 W	80	
	145-9955	LED-6/12W/2700K	1224.7 lm	12 W	80	
	145-9955	LED-6/12W/2700K	1224.7 lm	12 W	80	
	 <p>[EE]</p>	145-9957	LED-6/12W/3000K	1315.4 lm	12 W	80
145-9957		LED-6/12W/3000K	1315.4 lm	12 W	80	
145-9959		LED-6/12W/4000K	1406.2 lm	12 W	80	
145-9959		LED-6/12W/4000K	1406.2 lm	12 W	80	
145-9956		LED-6/18W/2700K	1701 lm	18 W	80	
145-9956		LED-6/18W/2700K	1701 lm	18 W	80	
145-9958		LED-6/18W/3000K	1837.1 lm	18 W	80	
145-9958		LED-6/18W/3000K	1837.1 lm	18 W	80	
145-9960		LED-6/18W/4000K	1950.5 lm	18 W	80	
145-9960		LED-6/18W/4000K	1950.5 lm	18 W	80	
145-7326		LED-6/26W/2700K	2258.5 lm	26 W	80	
145-7326		LED-6/26W/2700K	2258.5 lm	26 W	80	
145-7327		LED-6/26W/3000K	2388.8 lm	26 W	80	
145-7327		LED-6/26W/3000K	2388.8 lm	26 W	80	
145-7328		LED-6/26W/4000K	2497.4 lm	26 W	80	
145-7328		LED-6/26W/4000K	2497.4 lm	26 W	80	
 <p>[EES]</p>		145-9961	LED-6/12W/2700K	1259.7 lm	12 W	80
		145-9961	LED-6/12W/2700K	1259.7 lm	12 W	80
	145-9963	LED-6/12W/3000K	1353 lm	12 W	80	
	145-9963	LED-6/12W/3000K	1353 lm	12 W	80	
	145-9965	LED-6/12W/4000K	1446.3 lm	12 W	80	
	145-9965	LED-6/12W/4000K	1446.3 lm	12 W	80	
	145-9962	LED-6/18W/2700K	1749.6 lm	18 W	80	

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	145-9962	LED-6/18W/2700K	1749.6 lm	18 W	80
	145-9964	LED-6/18W/3000K	1889.5 lm	18 W	80
	145-9964	LED-6/18W/3000K	1889.5 lm	18 W	80
	145-9966	LED-6/18W/4000K	2006.2 lm	18 W	80
	145-9966	LED-6/18W/4000K	2006.2 lm	18 W	80
	145-7329	LED-6/26W/2700K	2319.7 lm	26 W	80
	145-7329	LED-6/26W/2700K	2319.7 lm	26 W	80
	145-7330	LED-6/26W/3000K	2453.5 lm	26 W	80
	145-7330	LED-6/26W/3000K	2453.5 lm	26 W	80
	145-7331	LED-6/26W/4000K	2565 lm	26 W	80
	145-7331	LED-6/26W/4000K	2565 lm	26 W	80
	145-9949	LED-6/12W/2700K	1162.6 lm	12 W	80
	145-9949	LED-6/12W/2700K	1162.6 lm	12 W	80
	145-9951	LED-6/12W/3000K	1248.7 lm	12 W	80
	145-9951	LED-6/12W/3000K	1248.7 lm	12 W	80
	145-9953	LED-6/12W/4000K	1334.9 lm	12 W	80
	145-9953	LED-6/12W/4000K	1334.9 lm	12 W	80
	145-9950	LED-6/18W/2700K	1614.8 lm	18 W	80
	145-9950	LED-6/18W/2700K	1614.8 lm	18 W	80
	145-9952	LED-6/18W/3000K	1743.9 lm	18 W	80
	145-9952	LED-6/18W/3000K	1743.9 lm	18 W	80
	145-9954	LED-6/18W/4000K	1851.6 lm	18 W	80
	145-9954	LED-6/18W/4000K	1851.6 lm	18 W	80
	145-7323	LED-6/26W/2700K	2179.3 lm	26 W	80
	145-7323	LED-6/26W/2700K	2179.3 lm	26 W	80
	145-7324	LED-6/26W/3000K	2305 lm	26 W	80
	145-7324	LED-6/26W/3000K	2305 lm	26 W	80
	145-7325	LED-6/26W/4000K	2409.8 lm	26 W	80
	145-7325	LED-6/26W/4000K	2409.8 lm	26 W	80



[M]