

Description

RGBW/RGBA Colour Changer. IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed LED circuit board, Colour Boost Technology. DMX interface. Knuckle permits 328° rotation, forward tilt 63° and backward tilt 110°. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. One cable entry.

Optical accessories are factory-installed. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy		
Lens	Safety glass lens		
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware		
Ingress protection	IP66		
Impact resistance	IK08		
Corrosion resistance	5CE		






Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	DMX
Power factor	> 0.9
Surge protection	SP10
Energy efficiency	D-E (Light source)




Additional information

Windage	0,01 m ²
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution	Colour temperature	Nominal Watt
 [B]	48WRGBA	12 W 48 W
 [M]	 3000K	
 [EE]	 4000K	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	145-0558	LED-2/12W/48WRGBA	2830.7 lm	12 W	20
	145-0555	LED-12/48W/3000K	3158.9 lm	48 W	20
	145-0552	LED-12/48W/4000K	3158.9 lm	48 W	20
[B]					
	145-0560	LED-2/12W/48WRGBA	3274.9 lm	12 W	20
	145-0557	LED-12/48W/3000K	3654.6 lm	48 W	20
	145-0554	LED-12/48W/4000K	3654.6 lm	48 W	20
[EE]					
	145-0559	LED-2/12W/48WRGBA	3543.9 lm	12 W	20
	145-0556	LED-12/48W/3000K	3954.8 lm	48 W	20
	145-0553	LED-12/48W/4000K	3954.8 lm	48 W	20
[M]					