

Description

RGBW/RGBA Colour Changer. IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed LED circuit board, Colour Boost Technology. DMX interface. Knuckle permits 350° rotation, forward tilt 39° and backward tilt 93°. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. One cable entry.

Optical accessories are factory-installed. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Safety glass lens			
Colors	RAL8019	RAL9004	RAL9007	RAL9016
	Grey brown	Signal black	Grey aluminium	Traffic white
Gasket	Silicone CCG® Controlled Compression Gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK08			
Corrosion resistance	5CE			




Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	DMX
Surge protection	SP10
Energy efficiency	D-E (Light source)




Additional information

Windage	0,01 m ²
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution	Color temperature	Nominal Watt
 [W] bi-symmetric, wide beam	4000K+RGBW	48 W
 [VN] symmetric, very narrow beam	RGBA	
 [M] symmetric, medium beam		

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	145-0435_us	LED-12/48W/4000K+RGBW	3954.8 lm	48 W	20
	145-0625_us	LED-12/48W/RGBA	3543.9 lm	48 W	20
[M] symmetric, medium beam					
	145-0436_us	LED-12/48W/4000K+RGBW	3654.6 lm	48 W	20
	145-0626_us	LED-12/48W/RGBA	3274.9 lm	48 W	20
[VN] symmetric, very narrow beam					
	145-0434_us	LED-12/48W/4000K+RGBW	3158.9 lm	48 W	20
	145-0624_us	LED-12/48W/RGBA	2830.7 lm	48 W	20
[W] bi-symmetric, wide beam					