FLC331 Surface mounted



Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Knuckle permits 350° rotation, forward tilt 39° and backward tilt 93°.Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. One cable entry.Optical accessories are factory-installed. To be specified at time of ordering.

WE-EF LEUCHTEN GmbH
Töpinger Straße 16, 29646 Bispingen, Germany - Phone: +49 5194 909-0
info@we-ef.com - https://we-ef.com

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	RAL7016 Anthracite grey; RAL9004 Signal black; RAL9006 White aluminium; RAL9007 Grey aluminium; RAL9016 Traffic white
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	DALI
Power factor	> 0.9
Surge protection	SP10 optional
Energy efficiency	C-D (Light source)

Additional information

Windage	0,01 m^2
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution

[B] symmetric, wide beam

[M] symmetric, medium beam

[EE] symmetric, very narrow beam

[EES] symmetric, very narrow beam, sharp cut-off

Colour temperature

2700K

3000K

4000K

Nominal Watt

24 W

36 W

52 W

WE-EF LEUCHTEN GmbH
Töpinger Straße 16, 29646 Bispingen, Germany - Phone: +49 5194 909-0
info@we-ef.com - https://we-ef.com

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[B] symmetric, wide beam	145-0395	LED-12/24W/2700K	2213.9 lm	24 W	80
	145-0407	LED-12/24W/3000K	2377.9 lm	24 W	80
	145-0419	LED-12/24W/4000K	2541.9 lm	24 W	80
	145-0399	LED-12/36W/2700K	3074.9 lm	36 W	80
	145-0411	LED-12/36W/3000K	3320.9 lm	36 W	80
	145-0403	LED-12/52W/2700K	4263.9 lm	52 W	80
	145-0415	LED-12/52W/3000K	4509.9 lm	52 W	80
	145-0427	LED-12/52W/4000K	4714.9 lm	52 W	80
	145-0427	LED-12/52W/4000K	4714.9 lm	52 W	80
[EE] symmetric, very narrow beam	145-0397	LED-12/24W/2700K	2616.9 lm	24 W	80
	145-0409	LED-12/24W/3000K	2810.7 lm	24 W	80
	145-0421	LED-12/24W/4000K	3004.6 lm	24 W	80
	145-0401	LED-12/36W/2700K	3634.6 lm	36 W	80
	145-0413	LED-12/36W/3000K	3925.3 lm	36 W	80
	145-0405	LED-12/52W/2700K	5039.9 lm	52 W	80
	145-0417	LED-12/52W/3000K	5330.7 lm	52 W	80
	145-0429	LED-12/52W/4000K	5573 lm	52 W	80
[EES] symmetric, very narrow beam, sharp cut-off	145-0398	LED-12/24W/2700K	2245.1 lm	24 W	80
	145-0410	LED-12/24W/3000K	2245.1 lm	24 W	80
	145-0422	LED-12/24W/4000K	2540.5 lm	24 W	80
	145-0402	LED-12/36W/2700K	3072.2 lm	36 W	80
	145-0414	LED-12/36W/3000K	3072.2 lm	36 W	80
	145-0406	LED-12/52W/2700K	3781.2 lm	52 W	80
	145-0418	LED-12/52W/3000K	3781.2 lm	52 W	80
	145-0430	LED-12/52W/4000K	4312.9 lm	52 W	80
[M] symmetric, medium beam	145-0396	LED-12/24W/2700K	2759.4 lm	24 W	80
	145-0408	LED-12/24W/3000K	2963.8 lm	24 W	80
	145-0420	LED-12/24W/4000K	3168.2 lm	24 W	80
	145-0400	LED-12/36W/2700K	3832.5 lm	36 W	80
	145-0412	LED-12/36W/3000K	4139.1 lm	36 W	80
	145-0404	LED-12/52W/2700K	5314.4 lm	52 W	80
	145-0416	LED-12/52W/3000K	5621 lm	52 W	80
	145-0428	LED-12/52W/4000K	5876.5 lm	52 W	80

WE-EF LEUCHTEN GmbH
Töpinger Straße 16, 29646 Bispingen, Germany - Phone: +49 5194 909-0
info@we-ef.com - https://we-ef.com
Subject to technical changes and errors. - Generated on 01/05/2026