

Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Knuckle permits 350° rotation, forward tilt 42° and backward tilt 99°. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

One cable entry. Optical accessories are factory-installed. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy		
Lens	Safety glass lens		
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware		
Ingress protection	IP66		
Impact resistance	IK08		
Corrosion resistance	5CE		








Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	DALI
Power factor	> 0.9
Surge protection	
Energy efficiency	D-E (Light source)




Additional information

Windage	0,025 m ³
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution	Colour temperature	Nominal Watt
 [B]	 2200K	48 W
		72 W
 [M]	 2700K	
 [EE]	 3000K	
	 4000K	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B]	145-0437	LED-24/48W/2200K	4358.6 lm	48 W	70
	145-0449	LED-24/48W/2700K	4358.6 lm	48 W	80
	145-0461	LED-24/48W/3000K	4681.5 lm	48 W	70
	145-0473	LED-24/48W/4000K	5004.3 lm	48 W	70
	145-0453	LED-24/72W/2700K	6053.6 lm	72 W	70
	145-0465	LED-24/72W/3000K	6537.9 lm	72 W	80
	145-0477	LED-24/72W/4000K	6941.5 lm	72 W	70
 [EE]	145-0451	LED-24/48W/2700K	5306.4 lm	48 W	80
	145-0463	LED-24/48W/3000K	5699.4 lm	48 W	70
	145-0475	LED-24/48W/4000K	6092.5 lm	48 W	70
	145-0455	LED-24/72W/2700K	7370 lm	72 W	70
	145-0467	LED-24/72W/3000K	7959.6 lm	72 W	80
	145-0479	LED-24/72W/4000K	8450.9 lm	72 W	70
 [M]	145-0450	LED-24/48W/2700K	5311.4 lm	48 W	80
	145-0462	LED-24/48W/3000K	5704.8 lm	48 W	70
	145-0474	LED-24/48W/4000K	6098.2 lm	48 W	70
	145-0454	LED-24/72W/2700K	7376.9 lm	72 W	70
	145-0466	LED-24/72W/3000K	7967.1 lm	72 W	80
	145-0478	LED-24/72W/4000K	8458.9 lm	72 W	70