

### Description

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Ingress protection	IP66			
Impact resistance	IK07			






### Electrical description

Power supply	120-277V / 50-60 Hz
--------------	---------------------




### Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	LED >60,000 h Ta 25°(L70/B10) Control gear >50,000 h Ta 25°

**Options**

Light distribution	Color temperature	Nominal Watt
 [VN] symmetric, very narrow beam	 3000K	6 W
 [VNS] symmetric, very narrow beam, sharp cut-off	 4000K	
 [M] symmetric, medium beam		

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	145-9791_us	LED-3/6W/3000K	696.3 lm	6 W	80
	145-9795_us	LED-3/6W/4000K	744.3 lm	6 W	80
[M] symmetric, medium beam					
	145-9792_us	LED-3/6W/3000K	650.7 lm	6 W	80
	145-9796_us	LED-3/6W/4000K	695.6 lm	6 W	80
[VN] symmetric, very narrow beam					
	145-9793_us	LED-3/6W/3000K	700.7 lm	6 W	80
	145-9797_us	LED-3/6W/4000K	749 lm	6 W	80
[VNS] symmetric, very narrow beam, sharp cut-off					