

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-shielded compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

2700 K option available on request.

Specifications

Material description

Body	Marine-grade die-cast aluminium alloy						
Lens	Safety glass lens						
Colours	<table><tr><td>RAL9004</td><td>RAL9006</td><td>RAL9007</td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Grey aluminium</td></tr></table>	RAL9004	RAL9006	RAL9007	Signal black	White aluminium	Grey aluminium
RAL9004	RAL9006	RAL9007					
Signal black	White aluminium	Grey aluminium					
Gasket	Silicone CCG® Controlled Compression Gasket						
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)						
Impact resistance	IK07						
Corrosion resistance	5CE+Primer						

Electrical description


Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.


Additional information


Options

Light distribution

 [M] symmetric, medium beam


 [B] symmetric, wide beam

 [EE] symmetric, very narrow beam

 [EES] symmetric, very narrow beam, sharp cut-off

Colour temperature





 3000K

 4000K

Nominal Watt

12 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	145-9493	LED-6/12W/3000K	1148.3 lm	12 W	80
	145-9494	LED-6/12W/4000K	1227.5 lm	12 W	80
[B] symmetric, wide beam					
	145-9495	LED-6/12W/3000K	1393.4 lm	12 W	80
	145-9496	LED-6/12W/4000K	1489.5 lm	12 W	80
[EE] symmetric, very narrow beam					
	145-9497	LED-6/12W/3000K	1492.9 lm	12 W	80
	145-9498	LED-6/12W/4000K	1595.9 lm	12 W	80
[EES] symmetric, very narrow beam, sharp cut-off					
	145-9491	LED-6/12W/3000K	1454.1 lm	12 W	80
	145-9492	LED-6/12W/4000K	1554.3 lm	12 W	80
[M] symmetric, medium beam					