

### Description

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Two cable entries.

Knuckle permits 350° horizontal and 180° vertical aiming of optics.

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction								
Lens	Safety glass lens								
Colours	<table><tr><td><b>RAL9004</b></td><td><b>RAL9016</b></td><td><b>RAL7016</b></td><td><b>RAL9007</b></td></tr><tr><td>Signal black</td><td>Traffic white</td><td>Anthracite grey</td><td>Grey aluminium</td></tr></table>	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL7016</b>	<b>RAL9007</b>	Signal black	Traffic white	Anthracite grey	Grey aluminium
<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL7016</b>	<b>RAL9007</b>						
Signal black	Traffic white	Anthracite grey	Grey aluminium						
Gasket	Silicone CCG® Controlled Compression Gasket								
Fasteners	PCS hardware								
Impact resistance	IK07								
Corrosion resistance	5CE								








### Electrical description

Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
------------------	---





### Additional information

Listings	Knuckle permits 350° horizontal and 180° vertical aiming of optics
----------	--

**Options**

Light distribution	Colour temperature	Nominal Watt
 [M]	 3000K	12 W
		18 W
 [EE]	 4000K	
 [B]	 2700K	
 [EES]		

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [B]	145-7141	LED-6/12W/2700K	1069.1 lm	12 W	80
	145-9586	LED-6/12W/3000K	1148.3 lm	12 W	80
	145-9587	LED-6/12W/4000K	1227.5 lm	12 W	80
	145-7159	LED-6/18W/2700K	1924.9 lm	18 W	80
	145-9886	LED-6/18W/3000K	2018.8 lm	18 W	80
	145-9887	LED-6/18W/4000K	2112.7 lm	18 W	80
 [EE]	145-7142	LED-6/12W/2700K	1297.3 lm	12 W	80
	145-9582	LED-6/12W/3000K	1393.4 lm	12 W	80
	145-9585	LED-6/12W/4000K	1489.5 lm	12 W	80
	145-7160	LED-6/18W/2700K	2064.9 lm	18 W	80
	145-9884	LED-6/18W/3000K	2165.6 lm	18 W	80
	145-9885	LED-6/18W/4000K	2266.4 lm	18 W	80
 [EES]	145-7143	LED-6/12W/2700K	1390 lm	12 W	80
	145-9588	LED-6/12W/3000K	1492.9 lm	12 W	80
	145-9589	LED-6/12W/4000K	1595.9 lm	12 W	80
 [M]	145-7140	LED-6/12W/2700K	1353.8 lm	12 W	80
	145-9581	LED-6/12W/3000K	1454.1 lm	12 W	80
	145-9581	LED-6/12W/3000K	1454.1 lm	12 W	80
	145-9584	LED-6/12W/4000K	1554.3 lm	12 W	80
	145-9584	LED-6/12W/4000K	1554.3 lm	12 W	80
	145-7158	LED-6/18W/2700K	2066.4 lm	18 W	80
	145-9882	LED-6/18W/3000K	2167.2 lm	18 W	80
	145-9883	LED-6/18W/4000K	2268 lm	18 W	80