

Description

IP66, Class I. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Two-sided light output versions for 360° symmetric distribution.

One-sided light output versions with 'rearward glow' feature. Ideal for pathway lighting applications. Luminaire spacing up to 5-8 m.

Specifications

Material description

| | | | |
|----------------------|--------------------------------|-----------------------------------|----------------------------------|
| Colours | RAL9004 Signal black | RAL9006 White aluminium | RAL9007 Grey aluminium |
| Ingress protection | IP66 | | |
| Impact resistance | IK10 | | |
| Corrosion resistance | 5CE+Primer | | |

Electrical description

| | |
|-------------------|--|
| Power supply | 230V / 50 Hz |
| Surge protection | 10/10kV (SP10) available on request |
| Energy efficiency | The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. |

Additional information

Options**Light distribution**

[C60] symmetric distribution



[R65] rectangular, side throw

Colour temperature

3000K



4000K

Nominal Watt



18 W

26 W

9 W

13 W

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|---|----------|-----------------|--------------|-------------------|-----|
|  [C60] symmetric distribution | 114-9071 | LED-6/18W/3000K | 825 lm | 18 W | 80 |
| | 114-9072 | LED-6/18W/4000K | 863.4 lm | 18 W | 80 |
| | 114-9073 | LED-6/26W/3000K | 1055.3 lm | 26 W | 80 |
| | 114-9074 | LED-6/26W/4000K | 1103.3 lm | 26 W | 80 |
|  [R65] rectangular, side throw | 114-9065 | LED-3/9W/3000K | 519.7 lm | 9 W | 80 |
| | 114-9066 | LED-3/9W/4000K | 543.9 lm | 9 W | 80 |
| | 114-9067 | LED-3/13W/3000K | 664.7 lm | 13 W | 80 |
| | 114-9068 | LED-3/13W/4000K | 694.9 lm | 13 W | 80 |