

Description

IP66, Class I, IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection including PCS hardware. Polycarbonate lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

Two-sided light output versions for 360° symmetric distribution.
One-sided light output versions with 'rearward glow' feature. Ideal for pathway lighting applications.

Luminaire spacing up to 5-8 m.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9016 Traffic white	RAL7016 Anthracite grey	RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket			
Ingress protection	IP66			
Impact resistance	IK10			

Electrical description

Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
------------------	---

Additional information

Options**Light distribution**

[C60] symmetric distribution



[R65] rectangular, side throw

Colour temperature

3000K



4000K



2700K

Nominal Watt



18 W

26 W

9 W

13 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60] symmetric distribution	114-9077	LED-6/18W/2700K	786.7 lm	18 W	80
	114-9071	LED-6/18W/3000K	825 lm	18 W	80
	114-9072	LED-6/18W/4000K	863.4 lm	18 W	80
	114-9078	LED-6/26W/2700K	997.7 lm	26 W	80
	114-9073	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-9074	LED-6/26W/4000K	1103.3 lm	26 W	80
 [R65] rectangular, side throw	114-9075	LED-3/9W/2700K	495.5 lm	9 W	80
	114-9065	LED-3/9W/3000K	519.7 lm	9 W	80
	114-9066	LED-3/9W/4000K	543.9 lm	9 W	80
	114-9076	LED-3/13W/2700K	628.5 lm	13 W	80
	114-9067	LED-3/13W/3000K	664.7 lm	13 W	80
	114-9068	LED-3/13W/4000K	694.9 lm	13 W	80