

Description

Ideal for pathway lighting applications.

IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate lens. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. Advanced thermal management protects LEDs while optimizing lumens output. 0-10V Dimming comes standard with luminaire. Luminaire head is factory-sealed and does not need to be opened during installation.

Two-sided light output versions for 360° symmetric distribution; one-sided light output versions with 'rearward glow' feature. Luminaire spacing up to 16-26 ft.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, all-aluminum construction			
Colors	RAL9004 Signal black	RAL9016 Traffic white	RAL8019 Grey brown	RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket			
Ingress protection	IP66			
Impact resistance	IK10			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	Integral 10kV Surge Protector
Energy efficiency	This is a new product release and may have an extended lead time.

Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	LED >60,000 h Ta 25°(L70/B10) Control gear >50,000 h Ta 25°

Options

Light distribution



[C60] symmetric distribution



[R65] Type IV Medium

Color temperature



3000K



4000K



2700K

Nominal Watt



18 W

26 W

9 W

13 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[C60] symmetric distribution</p>	114-9077	LED-6/18W/2700K	786.7 lm	18 W	80
	114-9071_us	LED-6/18W/3000K	825 lm	18 W	80
	114-9072_us	LED-6/18W/4000K	863.4 lm	18 W	80
	114-9078	LED-6/26W/2700K	997.7 lm	26 W	80
	114-9073_us	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-9074_us	LED-6/26W/4000K	1103.3 lm	26 W	80
	 <p>[R65] Type IV Medium</p>	114-9075	LED-3/9W/2700K	495.5 lm	9 W
114-9065_us		LED-3/9W/3000K	519.7 lm	9 W	80
114-9066_us		LED-3/9W/4000K	543.9 lm	9 W	80
114-9076		LED-3/13W/2700K	628.5 lm	13 W	80
114-9067_us		LED-3/13W/3000K	664.7 lm	13 W	80
114-9068_us		LED-3/13W/4000K	694.9 lm	13 W	80