

### Description

IP66, Class I. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Two-sided light output versions for 360° symmetric distribution.

One-sided light output versions with 'rearward glow' feature. Ideal for pathway lighting applications. Luminaire spacing up to 5-8 m.

## Specifications

### Material description

---

Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9007</b> Grey aluminium
Ingress protection	IP66		
Impact resistance	IK10		
Corrosion resistance	5CE+Primer		

---

### Electrical description





---

Power supply	230V / 50 Hz
Surge protection	10/10kV (SP10) available on request
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.



---

### Additional information

**Options**

Light distribution	Colour temperature	Nominal Watt
 [C60]	 3000K	18 W 26 W
 [R65]	 4000K	9 W 13 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60]	114-9071	LED-6/18W/3000K	825 lm	18 W	80
	114-9072	LED-6/18W/4000K	863.4 lm	18 W	80
	114-9073	LED-6/26W/3000K	1055.3 lm	26 W	80
	114-9074	LED-6/26W/4000K	1103.3 lm	26 W	80
 [R65]	114-9065	LED-3/9W/3000K	519.7 lm	9 W	80
	114-9066	LED-3/9W/4000K	543.9 lm	9 W	80
	114-9067	LED-3/13W/3000K	664.7 lm	13 W	80
	114-9068	LED-3/13W/4000K	694.9 lm	13 W	80